

# rs232 / Lan

TM-AA-5D

## □□□

□□□□□□16□□□□□□□□□□PLU□□□□16□□□□□□□□□□□□□□□□;

□□□□□□□□□□;

□□□□□□□□□□;

□□□□□□□□□□;

□□□□□□□□□□□□□□□□□□□□□□□□□□□□;

□□□□□□□□□□;

□□□□□□□□□□;

□□□□□□□□□□PC□□□□□□;

## □□□

□□□□	□□□ 4000 PLU			
PLU□□□□□□	□□3□□□□□;□□3□□□□□□□□□□POS□□□□;□□4□□□□□□□□			
□□□□□□	71			
□□□□□□	□□□□□□22□□□□□□			
□□□□□	□□□32□□□□□			
□□□□	3000			
□□□	□□-10~ + 55°C;□□□□0~ + 40°C			
□□□	≤85□RH			
□□□	AC 220V□50 HZ			
□□□□□	□□□LED			
□□□	□□5□□□□□5□□□□□7□□			
□□□□□	30□□-60□□			
□□□□□	75□□/□			
□□□	RS232□□□□□□□□□□□□□□□□□□□□□□			
□□	381 * 428 * 500□□			
□□				
□□□□	3□□	6□□	15□□	30□□
□□□□	1□	2□	5□	10□
□□	1/3000	1/3000	1/3000	1/3000
□□□□	20□	40□	100□	200□

