

usb□□□□□□

□□□□ ECD-410D□

□□□

4□5□□□□□□□□□8□□□□□□□□□□
□□□□□□□□□□□□□□□□□□□□□□
9V□24V□□□□
□□□□□□□□□□
3□□

□□□

□□	□□□0.8□□SPCC□□□□□□□□□□□□□□
	□□□1.0mm SECC□□□□□□
□□□□	□□pos itions□□□85/84/84/85 mm
	□□pos ition□□□68/67/67/67/68 mm
	□□□193□□;□□□59□□
□□	8□□□□Pos ition□□□82;□□□57;□□□46
□□	3□□
□□	12V 24V□□□□
□□	□□□□□□□□□□□□
□□	RJ11 / RJ12
□□	□□□□
□□	6.5□□□□□□□7.0□□□□□□□□
□□□□	410□□□□x 415□□□□x 100□□□□□□□□10□□□□

□□□□□



ECD-410D



www.ocominc.com





www.ocominc.com





Application Area

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf



usb