#### 16bit Auto-Sense-Handheld-Barcode-Scanner mit Standfuß

(M / N: OCBS-LA04)

#### Feature:

- 1.Auto-Induktion eingebaut, grün-Design;
- 2. Hohe Abtastrate und Abstand lange Messwert;
- 3. Excellent Entschlüsselungsfähigkeit;
- 4.KBW, RS232 und USB unterstützt;
- 5. Durable Konstruktion mit Zukunftssicherheit kombiniert;

#### **SPEZIFIKATION:**

Leistungsmerkmale	
Lichtquelle:	Sichtbare Laser (650-670nm)
Scan-Rate:	100 Scans pro Sekunde
Leseabstand	2,5 ~ 600 mm (100% UPC / EAN)
Scannertyp:	Bidirektionales
Lösung:	0.10mm (4mm) bei PCS 0.9
Druckkontrast Minimum:	20%, minimale Reflexionsdifferenz (@ 650 nm)
Dekodierfähigkeit:	UPC / EAN, UPC / EAN mit Supplementals, UCC / EAN-128, Code 39, Code 39 Voll ASCII, Code 39 TriOptic, Code 128, Code 128 vollständige ASCII, codabar, verschachtelt 2 von 5, diskrete 2 von 5, Code 93, MSI, Code 11, ATA, RSS Varianten, Chinesen 2 von 5
Physikalische Eigenschaft	
Unterstützte	PS2, RS232, USB
Schnittstellen:	
Stromspannung:	DC + 5V +/- 5%
Strom:	100 mA
Ruhestrom:	&Ampere Lt;40 mA
Energiequelle:	Host-Leistung oder extern (RS232) Stromversorgung
Scannen-Winkel	Neigung 45 ° Elevation 60 °
Maße:	L165.42mm X W69.72mm X H89.67mm
Gewicht:	140g (ohne Standfuß)
Stand	Mit
Farbe:	Elfenbein und Schwarz
Benutzerumgebung	
Betriebstemperatur:	0 Grad C ~50 Grad C
Lagertemperatur:	$-40$ Grad C $\sim 70$ Grad C
Feuchtigkeit:	5 ~ 95% relative Luftfeuchtigkeit, nicht kondensierend
Elektrostatische	Cestätigen 15KV Luftentladung zu +/- und +/- 8 kV Kontaktentladung
Entladung:	
Drop-Spezifikationen:	Beständig gegen mehrere 1,5m Höhe auf Beton
Safe:	
EMI / RFI:	FCC Klasse A und CE
Lasersicherheit:	CDRH Laserklasse 2



# Product Picture











# All-round show





### Parameter

Visible laser (650-670nm)
100 scans per second
2.5 ~600mm (100% UPC/EAN)
Bi-directional ATT
0.10mm (4mil) at PCS 0.9
20%, minimum reflective difference (@650nm)
UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5

interiaces oupported.	F02, N0202, U0D
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	With
Color:	Ivory and black
User Environment	
Operating Temperature:	0℃~50℃
Storage Temperature:	0-40°C~70°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge  Withstands multiple 1.5m drops to concrete
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product
CONTRACTOR DESCRIPTION OF THE PARTY OF THE P	

## Shipping and payment

- Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
- EXPRESS: around 3-7 working days to arrive
- INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which tination port

  By sea: depend on which destination port

  T/T destination port
- 4. By sea: depend on which destination port
- 5. T/T
- Western Union

### **Company Profile**



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.











