Mini Wireless-Barcode-Scanner

(Modell:OCBS-W700)

TECHNISCHE DATEN:

PHYSIKALISCHE characterstics	
Lichtquelle:	Visible Red Laser 650 nm
Scanner Abmessungen:	160mm * 70mm * 40mm(W * H * D)
Gewicht:	300G
Material:	ABS + PC
Scanning-Modus:	Eine Zeile Scannen; Hand / Automatik
Anzeige Way:	Summer und Leuchtanzeige
PERFORMANCE characterstics	
Breite des Scanfelds:	20mm @ Scannerfenster 260mm @ 260mm
Tiefe des Scanfelds:	4mm (0,1 mm) / 5-60mm 5mil (0,12 mm) / 10-100mm 10 mil (0,25 mm) / 15-250mm 35mil (0,89 mm) / 140-600mm 43mil (1,1 mm) / 150-800mm
Scangeschwindigkeit:	120 Scans / Sek
Scan-Präzision:	0,10 mm (pcs0.9)
Drucken Kontrast:	Mindestens 30% Reflektionsdifferenz
Error Rate:	1 / (6 Millionen)
Decodiermöglichkeiten:	Internationale allgemeinen 1D-Barcodes
Aktuell:	60mA (Arbeits-); □5uA (Standby)
Scannen Corner:	32 °
Scannen Höhe:	68 °
Scanwinkel von Avertence:	52 °
Arbeitsfrequenz:	2,4 GHz
Kommunikation Entfernung:	100m (Offene Places) 20m (Innen)
Kommunikationsschnittstelle:	USB
Benutzerumgebung characterstics	
Drop-Spezifikation:	2m freien Fall
Laser Level:	Level-1-Lasersicherheitsnorm
Laden Leistung:	DC5V

Produktdetails:

Product Picture

Features

Simple but not easy

Integrated non-volatile memory (can store about 500 barcodes);

Outside communication distance can

reach 100m, inside is 20m;;

20 scanners can work in the same field without interfering each other;

Plug and play;

www.ocominc.com

800mA big capacity Li-battery.

All-round show

Parameter

PHYSICAL CHARACTERSTICS	
Light Source	Visible Red Laser 650 nm
Scanner Dimensions(W * H * D)	160mm * 70mm * 40mm
Weight	300G
Material	ABS + PC
Scanning Mode	One line scanning; Manual / Automatic
Indicator Way	Buzzer and Indicator Light
PERFORMANCE CHARACTERSTICS	
Width of Scan Field	20mm@scanner window 260mm@260mm
Depth of Scan Field	4mil (0.1mm)/5-60mm 5mil (0.12mm)/10-100mm 10mil (0.25mm)/15-250mm 35mil (0.89mm)/140-600mm 43mil (1.1mm)/150-800mm

Scan Speed	120 scans/sec
Scan Precision	0.10mm (pcs0.9)
Printing Contrast	Minimum 30% reflection difference
Error Rate	1/(6million)
Decode Capability	International general 1D barcodes
Current	60mA (working); ≦5uA(standby)
Scanning Corner	32°
Scanning Elevation	68°
Scanning Angle of Avertence	52°
Working Frequency	2.4GHz
Communication Distance	100m (Open Places) 20m (Indoor)
Communication Interface	USB
USER ENVIRONMENT CHARACTERSTICS	
Drop Specification	2m free fall
Laser Level	Level-1 laser safety standard
Charge Power	5VDC

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.
OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.
OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.
You can find more information of us at: www.ocominc.com,
Together we quest for the best.

Relevante Dokumente:

Wollen Sie mehr wissen wollen, Produkt informationen?Bitte Klicken Sie hier.

[Spezifikation]