#### **Mobil Positions-Maschine Laptop-Computer in China**

(Modell-Nr: TM1502)


#### **SPEZIFIKATION:**

LCD Bildschirm Größe	15"
Seitenverhältnis	4: 3
Lösung	1024 × 768
Pixel Pitch (mm)	0,297
Aktiv Fläche (mm)	304,1 × 228,1
Anzahl der Farben	16.2M
Kontrast Verhältnis	700/1
Helligkeit	250cd / m <sup>2</sup>
Blickwinkel	150/135
Reaktionszeit	8ms
Touch-Panel Größe	15" 4-Draht
Draußen Dimension	247mm × 322mm
Sichtfeld	235mm × 310mm
aktiver Bereich	228mm × 304mm
Oberfläche Härte	ЗН
optisch Klarheit	80%
Betriebs Temperatur	-10C ~ 60C
Ausdauer Test-Streiks	Zu Ende 10millions
Betriebs Stromspannung	DC5V
Widerstand	200Ω ~ 900Ω
Linearität	1,50%
Faceplate Oberfläche	Anti-Glanz Beschichtung, Glare-Beschichtung
Film Dicke	0,175 mm, 0.188mm
Glas Dicke	0,7mm, 1,1mm, 1,8mm
Betrieb Druck	20 ~ 150g
Lagerung Temperatur	-30 °C ~ 80 °C
Betriebs Strom	5mA ~ 25mA
Feuchtigkeit	& Lt; 95%
Isolierung Widerstand	20MΩ @ DC25V
Plombierbare gegen	Staub, Wasser, Öl, statisch

#### **Produktdetails:**







#### **Features**

### Simple but not easy

High resolution: Support 1024\*768 / 1280\*1024;







All-round show



Application Area



Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

Recreation: sauna, spa, night club, theme park, casino and

point of sales for lottery ticket

Commercial: information management terminals for parking

lot, inn, aviation, subway, station and wharf







#### Parameter

LCD Screen Size	15"	Marie I
Aspect Ratio	4:3	
Resolution	1024×768	
Pixel Pitch(mm)	0.297	
Active Area(mm)	304.1×228.1	
Number of colors	16.2M	-0
Contrast Ratio	700/1	an in Co
Brightness	250cd/m²	·40.000
Viewing Angle	150/135	M. c.
Response Time	8ms	

	Z-11,2
Touch Panel Size	15" 4-wire
Outside Dimension	247mm×322mm
Viewing area	235mm×310mm
Active area	228mm×304mm
Surface Hardness	3H
Optical Clarity	80%
Operating Temperature	-10C~60C
Endurance Test strikes	Over 10millions
Operating Voltage	DC5V
Resistance	2000~9000
Linearity	1.50%
Faceplate Surface	Anti-glare coating, glare coating
Film Thickness	0.175mm, 0.188mm
Glass Thickness	0.7mm, 1.1mm, 1.8mm
Operation Pressure	20~150g
Storage Temperature	-30°C ~80 °C
Operating Current	5mA~25mA
Humidity	<95%
Isolation Resistance	20MΩ @ DC25V
Sealable against	Dust ,water, oil , static



# Production Line





## Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
1	Thermal Printer	40,000 Sets / Month	250,000 Sets
1 500	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
1	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
1	Barcode Scanner	40,000 Sets / Month	20,000 Sets
1	POS Machine	5,000 Sets / Month	10,000 Sets
1	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets



#### Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfication.



Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

#### Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
1	Ageing Tester	No Information	6
A -CO.	Withstand Voltage Tester	CC2670A	1 30076
1	Oscilloscope	TBS1102	1
V	DC Power Supply	PS-305DM	6
V	Digital Torque Meter	HP100	1
1	Calliper	GUANGLU	2
1	Multi-meter	VC890D	7
1	Test Computer	No Information	13

#### Certifications



#### Packing and Shipment





#### Payment

Delica Co.



















#### Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have established goods relationship with our customers and have friendly communication with each other.





#### Why you choose us?



Flexible Cooperation

#### Company Profile

## This Assessed Supplier Has Been Independently Verified

Build Your Growth On Trust













OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matthe Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals. Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Eruope, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.





#### Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District,

Shenzhen 518054, China;

Websites: http://www.thermalprinter.com.cn; http://www.ocominc.com;

E-mail: ocom@ocominc.com , ocomtech@gmail.com ;

Skype: ocominc2000, ocominc;

MSN: ocomtech@hotmail.com, ocominc@hotmail.com;

Trademanager: szocominc, cn1500439666;

QQ: 2485890637,190852203; Tel/Fax: +86.755.8605.3207.



#### **Relevante Dokumente:**

Wollen Sie weitere Produkt-inf wissenormationen?Bitte Klick hier.

▼

**Spezifikation**