

Auto-Sense-Handlaser-Barcode-Scanner mit Stand  
(Modell: OCBS - L012)

**SPEZIFIKATIONEN:**

|                              |  |
|------------------------------|--|
| Leistungsmerkmale            |  |
| Lichtquelle:                 | Sichtbarer Laser (650-670nm)   |
| Scan-Rate:                   | 100 Scans pro Sekunde  |
| Leseabstand                  | 2,5 ~ 600mm (100% UPC / EAN)   |
| Scannertyp:                  | Bidirektional  |
| Auflösung:                   | 0,10 mm (4 mil) bei PCS 0,9  |
| Druck Kontrast Minimum:      | 30%, minimale Reflexionsdifferenz (@ 650nm)  |
| Fehlerrate:                  | 1/3000000  |
| Decodierfähigkeit:           | UPC / EAN, UPC / EAN mit Ergänzungen, UCC / EAN128, Code 39, Code 39 voller ASCII, Code 39 Trioptic, Code 128, Code 128 voller ASCII, Kodabar, Interleaved 2 von 5, Diskrete 2 von 5, Code 93, MSI , Code 11, ATA, RSS-Varianten, Chinesisch 2 von 5 ... |
| Physikalische Eigenschaften  |  |
| Unterstützte Schnittstellen: | PS2, RS232, USB  |
| Stromspannung:               | DC + 5V +/- 5%   |
| Strom:                       | 100 mA   |
| Leerlaufstrom:               | & lt; 40 mA  |
| Energiequelle:               | Host-Stromversorgung oder externe (RS232) Stromversorgung  |
| Scanwinkel                   | Neigung 45 ° Elevation 60 °  |
| Maße:                        | L165mm X W63mm X H87mm   |
| Gewicht:                     | 129g (ohne Ständer)  |
| Stand                        | Wahlweise  |
| Farbe:                       | Grau und Schwarz   |
| Benutzerumgebung             |  |
| Betriebstemperatur:          | 0 °C ~ 40 °C   |
| Lagertemperatur:             | -40 °C ~ 60 °C   |
| Feuchtigkeit:                | 5 ~ 95% relative Luftfeuchtigkeit, nicht kondensierend   |
| Elektrostatische Entladung:  | Bestätigen Sie die Luftentladung mit +/- 15KV und die Kontaktentladung mit +/- 8KV   |
| Tropfen Spezifikationen:     | Widersteht mehrere 1,5 m Tropfen auf Beton   |
| Sicher:                      |  |
| EMI / RFI:                   | FCC Klasse A und CE  |
| Lasersicherheit:             | CDRH Klasse 2 Laserprodukt   |

**Produktdetails:**



Product Picture





## ||| Features

***Simple but not easy***

Handheld laser barcode scanner



High scan rate (100 scans/sec) and long reading distance;



Excellent decode capability;



KBW, RS232 and USB supported;



Durable construction combined



with future-proofing;



Grey and Black Color available

## All-round show





## Parameter

| Performance Characteristics |   |
|-----------------------------|---|
| Light Source:               | Visible laser (650-670nm)   |
| Scan Rate:                  | 100 scans per second  |
| Reading Distance            | 2.5 ~600mm (100% UPC/EAN)   |
| Scanner Type:               | Bi-directional  |
| Resolution:                 | 0.10mm (4mil) at PCS 0.9  |
| Print Contrast<br>Minimum:  | 30%, minimum reflective difference (@650nm)   |
| Error Rate:                 | 1/3000000   |
| Decode Capability:          | UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5 |

| <b>Physical Characteristics</b> |  |
|---------------------------------|--|
| Interfaces Supported:           | PS2, RS232, USB  |
| Voltage:                        | DC+5V±5%   |
| Current:                        | 100 mA   |
| Idle Current:                   | <40 mA   |
| Power Source:                   | Host power or external (RS232) power supply                      |
| Scanning Angle                  | Inclination 45° Elevation 60°                                    |
| Dimensions:                     | L165mm X W63mm X H87mm   |
| Weight:                         | 129g (without stand)   |
| Stand                           | Optional   |
| Color:                          | Grey and black   |
| <b>User Environment</b>         |  |
| Operating Temperature:          | 0°C~40°C   |
| Storage Temperature:            | -40°C~60°C   |
| Humidity:                       | 5~95% relative humidity, non-condensing                          |
| Electrostatic Discharge:        | Confirm to +/-15KV air discharge and +/-8KV of contact discharge |
| Drop Specifications:            | Withstands multiple 1.5m drops to concrete                       |
| <b>Safe:</b>                    |  |
| EMI/RFI:                        | FCC Class A and CE   |
| Laser Safety:                   | CDRH class 2 laser product                                       |

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive

2. By sea: around 2-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com),  
Together we quest for the best.







Monica Fu



## OCOM Technologies Limited

Add: 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Tel: 0086.755.8605.3207 ext 801

Fax: 0086.755.8605.3207 ext 868

Web: [www.ocominc.com](http://www.ocominc.com)

E-mail: [sales01@ocominc.com](mailto:sales01@ocominc.com), [sales01@ocomtech.com.cn](mailto:sales01@ocomtech.com.cn)

Skype: [ocomsales01](https://www.skype.com/user/ocomsales01); MSN: [ocomsales01@hotmail.com](mailto:ocomsales01@hotmail.com)

Ali TM: [cn1001868228](https://www.aliexpress.com/item/cn1001868228); QQ: 1483705401

Mobile/Wechat/Whatsapp: 0086.189 4871 3992



Reliable One-Stop Supplier for POS and Auto-ID Related Products

**Relevante Dokumente:**

Möchten Sie mehr Produkt inf wissen?Ormation?Bitte Klick hier.

## **Spezifikation**

Benutzerhandbuch