Hochwertiger 433 MHz oder Bluetooth Wireless QR Code 2D Barcode Scanner mit Ständer

Artikelnummer: OCBS-W231-4/b

Features:
1, 433 MHz drahtlose Kommunikation Distanz 300 m Outdoor, Indoor 100 m; Die Entfernung zur Bluetooth-Wireless-Outdoor 20 m und 10 m Indoor;
2, ausgerüstet mit aufladen und Kommunikation
3, eine weiche Kunststoff-Abdeckung zum Schutz der Linse und eine Gliederung deutlich verbessert die Leistung von Anti-Drop;
4, Barcodes auf dem Bildschirm von Computern und Mobiltelefonen können gescannt werden;
5, Sie brauchen keine Treiber, Plug & Play;
6, kann mehr als 10 000 Stücke von Daten speichern;
7, mehrere Scanner können an einen Receiver (433 MHz) angeschlossen werden.

Parameter:

Mit einer Lichtquelle	617 nm LED
Lichtquelle Beleuchtung	625 nm LED
Scan-Winkel	39 ° (h) 25 ° (v)
Der Drehwinkel	0-360 ° c
Höhenmeter	65 ° c
Neigungswinkel	60 ° c
Kontrast drucken	Höher als 25%
1 d i	UPC/EAN, UPC/EAN mit supplementals, BooklandEAN, ISSN, Gutschein Extended Free Code128, EAN-128, ISBT 128, Code 39, Code 39 volle ASCII, Code 39 trioptic, Code 93, Code 32, Code11, Matrix 2 5, Interleaved 2 von 5, diskrete 2of 5, Codabar, MSI, 2, 5, Barvariants Daten, EAN, Koreanisch 3 5, ISBT verketten
2D	PDF417, PDF417, komplexe Codes, 39, DataMatrix, MaxiCode, QR-Code, Azteken, microqr
Schnittstelle	USB (Cable Wireless Receiver)
Reichweite	433 MHz: innen: 100 m; Außen: 300 m (Maximum) Bluetooth: innen: 10 m; Aussen: 20 m (max.)
Betriebstemperatur	-10 ° c-45 ° c
Lagertemperatur	-20 ° c-65 ° c
Luftfeuchtigkeit	5-85%
Feuchtigkeit-Inhalt während der Lagerung	5%-95%
Die Haltbarkeit der	Kann eine Vielzahl von 1,5 m bis Beton standhalten
Stromanschluss	5 v DC, 280mA
Ladezeit	6 Std.
Batterie	1500mAh
Luminanz	Innen: 3.000 Lux Max; Sonnenlicht: Max 86000 Lux
IP-Grade	IP42
Bereiche decodieren	

Eine typische Leistung *		Typische Einsatzbereiche	
		Focus Range HD	
Barcode-Typ	Die Dichte der Symbole	Nahe	Viel
Der Code 39	5,0 Meilen	5 mm	90 mm
100% der UPCA Barcodes	13,0 Meilen	bis 8 mm	200 mm
Der Code 39	20,0 Meilen	bis 8 mm	250 mm
PDF 417	6,8 Meilen	5 mm	95 mm
Die Data Matrix	10,0 Meilen	5 mm	110 mm
QR-Code für	20,0 Meilen	10 mm	150 mm
Auflösung 1 d-Code 39	4 Mio. mil		
Die Auflösung der 2D Data Matrix	10 MIL		
Material	ABS + PC		
Eine Dimension	Scanner (70 * 95 * 168 mm) base (145 * 112 * 74 mm)		
Nettogewicht	Tastkopf 185 g Base 186 g		
Bestellinformationen:	**OCBS-W231-4:** 2D Barcode Scanner Wireless 433 MHz von der Wiege		
	OCBS-W231-b: 2D Scanner mit barocde Bluetooth Cradle		

FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE

LONG DISTANCE WIRELESS COMMUNICATION

STRONG DECODING ABILITY

CHARGING CRADLE

STABLE STRUCTURE

NO NEED DRIVER, PLUG AND PLAY

1 FAST SCAN,HIGH RECOGNITION RATE

3 CRADLE FOR CHARGING AND WIRELESS COMMUNICATION

4 STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE

5 NO NEED DRIVER PLUG AND PLAY

The product family

Product packaging figure

WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER

PRODUCT INORMATION

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Barvariants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39,Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wirelless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside:20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base(145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.

Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: sales15@ocominc.com

Tel: 0086.755.86053207-815;

Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: ocomsales15;

Whatsapp: +0086.189.4879.9080;