


## OCBS-W232 USB Bluetooth Wireless Barcode Scanner

| PHYSICAL CHARACTERISTICS       |  |
|--------------------------------|--|
| Light Source                   | Visible Laser Diode (VLD) @ 650 nm                       |
| scanner Dimensions(W * H * D)  | 168*72*93 mm   |
| receiver Dimensions(W * H * D) | 130*75*129mm   |
| Material                       | ABS+TPU /Aluminium alloy                                 |
| scanner Weight                 | 190g (Including battery)                                 |
| receiver Weight                | 180g   |
| User Mode                      | Hand-held  |
| Scanning Mode                  | Manual/ Automatic  |
| Indicator Light                | Scanner LED Red and Blue receiver Left Green+ right Blue |
| Buzzer                         | Buzzer Volume Adjustable                                 |

| PERFORMANCE CHARACTERISTICS |   |
|-----------------------------|---|
| Width of Scan Field         | 60mm@30mm ( From engine face )<br>98mm@100mm ( from engine face )   |
| Depth of Scan Field         | 10-450mm (Contrast 0.9 Density0.25)   |
| Scan Speed                  | 300 scans/sec   |
| Scan Precision              | 0.10-0.825mm  |
| Bit Error Rate              | 1/(5million)  |
| Symbologies Supported       | 1D<br>UPC-A, UPC-E, EAN-8, EAN-13 Code 39, Code 32, Coda bar ,Code 128, ISBT 128, Code 93, Interleaved 2 of 5 Discrete 2 of 5 ,CODE11, MSI,  名称sey GS1-DataBar, UCC/EAN-128,BooklandEAN, Bookland EAN/ISBN , Trioptic Code39, CouponCodeGS1, DataBar-14, SETUP128 GS1Data Bar Limited, GS1Data Bar Expanded, RSS |
|                             | 2D<br>PDF417 DataMatrix(DM) QR  |
| Battery                     | 3.7V/1200mAh,Li-ion   |
| Charge Time                 | 2.5 Hours   |
| Scan Time                   | 10 Hours  |
| Scan Current                | 95mA  |
| Standby current             | 25mA  |
| Maximum Pitch Angles        | 60°   |
| Maximum Tilt Angles         | 45°   |
| Working Frequency           | 433MHz  |
| Communication Distance      | 200m (Open Places)  |
| Flash                       | 16MB  |
| Communication Interface     | USB   |