OCBS-W800 433MHz drahtlose tragbare Barcode-Scanner mit Gedächtnis

TECHNISCHE DATEN:

PHYSIKALISCHE characterstics	
Lichtquelle:	Visible Laser Diode (VLD) @ 650 nm
Scanner Abmessungen :	168mm * 72mm * 93mm (W * H * D)
Empfänger Maße:	130mm * 45mm * 129mm (B * H * D)
Stoff:	ABS + TPR / Aluminium-Legierung
Gewicht:	370g
Scan-Modus:	Hand; Kontinuierliche Scanmodus.
Kontrollleuchte:	LED rot und blau
Summer:	Buzzer Lautstärke einstellbar
PERFORMANCE characterstics	
Breite des Scan-Feld:	60mm @ 30mm (Von Motor Gesicht) 98mm @ 100mm (von Motor Gesicht)
Tiefe des Scanfeld:	10-450mm (Kontrast 0,9 Dichte 0,25)
Scangeschwindigkeit:	150 Scans / Sekunde
Scan Präzision:	0.10-0.825mm
Bit Error Rate:	1,5 Millionen)
Dekodierfähigkeit:	UPC / EAN, UPC / EAN mit Supplementals, UCC / EAN-128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 von 5, Code 93, MSI, Code 11, RSS Varianten, Chinesen 2 von 5, MSI / Plessey, UK / Plessey, UCC / EAN 128, Chinesisch-Code, GS1 DataBar (RSS) Serie
Batterie:	3,7V / 750mAh, Li-Ion
Aufladezeit:	3,0 Stunden
Scan-Zeit:	30 Stunden
Strom:	95mA (in Betrieb); 25mA (Standby)
Angles:	Pitch: 60 °; Tilt: 45 °
Arbeitsfrequenz:	433MHz
Kommunikation Entfernung:	200m (Open Places)
Kommunikationsinterface:	USB
Benutzerumgebung characterstics	
Temperatur:	-10degree Cto 45Grad C (Betrieb), -40degree Cto 60 Grad C (Storage)
Relative Luftfeuchtigkeit:	5% bis 90% (ohne Betauung)
Drop-Spezifikation:	Beständig auch bei wiederholtem 1,5 m Höhe auf Beton Oberfläche
Ambient Beleuchtung:	0 ~ 100.000 LUX
Elektrostatische Entladung:	Entspricht 12KV Luftentladung und ± 6 KV Kontaktentladung ±
Sicherheitszertifikat:	CE, FCC, Klasse 2, RoHS

Produktdetails:

Product Picture

Features

Simple but not easy

Integrated non-volatile memory

Data transmission distance reaches 200m in open area

Integrated non-volatile memory

Intelligent battery management system, real-time check the remaining battery

32bit decoder ensuring excellent decoding ability

All-round show

Parameter

PHYSICAL CHARACTERSTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm
Memory	128K
Scanner Dimensions(W * H * D)	168mm * 72mm * 93mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	370g
Scanning Mode	Hand-held; Continuous Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERSTICS	
Width of Scan Field	60mm@30mm（From engine face） 98mm@100mm（from engine face）
Depth of Scan Field	10-450mm（Contrast 0.9　Density 0.25）
Scan Speed	150 scans/sec

Scan Speed	[illegible]
Scan Precision	0.10-0.825mm
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese Code, GS1 DataBar (RSS) series
Battery	3.7V/750mAh,Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	95mA (working); 25mA(standby)
Angles	Pitch:60°; Tilt: 45°
Working Frequency	433MHz
Communication Distance	200m (Open Places)
Communication Interface	USB
USER ENVIRONMENT CHARACTERSTICS	
Temperature	-10℃ to 45℃ (Operating), -40℃to 60℃ (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow

8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.
OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.
OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.
You can find more information of us at: www.ocominc.com,
Together we quest for the best.

Relevante Dokumente:

Wollen Sie weitere Produkt-inf wissenormationen?Bitte Klick hier.

[Spezifikation]
[Handbuch]