

OCP-PP-M082: 3-Zoll-Mini-WiFi-Thermo-Belegdrucker

(Modell: OCP-PP-M082)

Eigenschaften:

- 1.Support von Windows, Java, Android oder IOS.
- 2.WIFI, USB und RS232-Kommunikation für Wahl.
- 3.Battery Ladeanzeige, einfach zu Ruhestrom kennen.
- 4.Higher Druckgeschwindigkeit 90 mm / sec.
- 5.100km TPH Leben.
- 6.Low Stromverbrauch und hoher Kapazität Lithium-Batterie.

Spezifikation:

Insgesamt Abmessungen (B × T × H)	98 × 103 × 45 mm
Gewicht	280g
Farbe	Schwarz
Effektive Druckbreite	72mm
Druckmethode	Thermisches Zeilendruck
Druckbefehle	ESC / POS kompatibel Befehlssatz
Druckgeschwindigkeit	Bis zu 90 mm / sec
Lösung	8 Punkte / mm (203 dpi)
Drucken Schrift	12x24 / 24x24
Säulenkapazität	32 Spalten / 16columns
Zeichengröße	1,5 x 3,0 mm (B x H) / 3.0x3.0mm (BxH)
Papierabmessungen	80,0 ± 0,1 mm x Durchmesser 30.0mm
Papierstärke	0,06 bis 0,08 mm
Zeichensatz	Alphanumerische / Chinesisch Kanji
Schnittstelle	USB, RS-232, WIFI (optional)
Datenpuffer	Bis zu 5 K Bytes
Netzteil	9V DC / 2A
Batterieleistung	7,4 V DC / 2000mA; Batterie kann durch für 4-5 Tage zu bleiben, wenn sie die volle Leistung, es drucken kann 120-150m Papier
Andere Eigenschaften	Papierererkennung, Stromerkennung, heruntergefahren Handbuch
Arbeitsbedingungen	Temperatur: -10 °C ~ 50 °C, Luftfeuchtigkeit: 10% ~ 90%
Lagerbedingungen	Temperatur: -20 °C ~ 70 °C, Luftfeuchtigkeit: 5% ~ 95%
Gerätename	Kann angepasst werden, Brief und Digital für Wahl, bei maximal 30 ASCII-Zeichen.
Passwort	Eintreten Standard-Pairing-Code "1234", kann es angepasst werden. Bei max 6 digitals.
Netzstecker Dimension	3,5 * 1,1 mm
Details zeigen	
<div style="border: 1px solid black; padding: 5px;"> <div style="display: flex; align-items: center;"> <div style="border: 1px solid black; width: 15px; height: 15px; margin-right: 5px; text-align: center; line-height: 15px;">x</div> <div style="border: 1px solid black; width: 15px; height: 15px; margin-right: 5px; text-align: center; line-height: 15px;">x</div> <div style="border: 1px solid black; width: 15px; height: 15px; margin-right: 5px; text-align: center; line-height: 15px;">x</div> <div style="border: 1px solid black; width: 15px; height: 15px; margin-right: 5px; text-align: center; line-height: 15px;">x</div> </div> </div>	



**80mm Bluetooth
Thermal Receipt Printer
for Andriod or IOS
OCPP-M082**



Product Picture





Features

Simple but not easy

Support Windows, Android,
or iPhone OS;



Bluetooth, USB and
RS232 communication.

Battery charge indicator, easy to know rest power.



Higher print speed 90mm/sec.



100km TPH Life.





Low power consumption
and large capacity
Lithium battery.

All-round show





Application Area

Bus/Taxi receipt, Traffic Citation, Logistics, Transportation, Warehouse management, Delivery, Illegal Parking Ticket, Drugstore, Food delivery, restaurant, Price Tag, Retail/Farm

Delivery



Restaurant



Bus / Taxi Receipt



Traffic Citation



Overall Dimension (W×D×H)	98×103×45mm
Weight	280g
Color	Black
Effective print width	72mm
Print method	Thermal line printing
Print commands	ESC/POS/STAR compatible command set
Print speed	Up to 90mm/sec
Resolution	8 dots/mm(203dpi)
Print font	12x24/ 24x24
Column capacity	48 columns/24 columns
Character size	1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(W x H)
Paper dimensions	80.0±0.1mm x diameter 30.0mm
Paper thickness	0.06 to 0.08mm
Character set	Alphanumeric/ Chinese Kanji ASCII Font A:12×24 Font B: 9x17 Korean code page 949
Communication Interface	USB/RS-232, Bluetooth
Flash	256KB
Power Adapter	9V DC/1.5A
Battery Power	7.4V DC/ 2000mA; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paper
Other features	Paper detection, power detection, Manual shut down
	Temperature:-10 degC ~ 50 degC Humidity:10% ~

Working conditions	Temperature: 5 degC ~ 40 degC, Humidity: 10% ~ 90%
Storage conditions	Temperature: -20 degC ~ 70 degC, Humidity: 5% ~ 95%
Device name	Can be customized, letter and digital for option, at max 30 ASCII characters.
Password	Enter default pairing code "1234", it can be customized. At max 6 digitals.
Power plug dimension	3.5*1.1mm

Paper Roll Installation



- A Open the printer cover.
- B Install the roller in the roll paper, and put them into the printer.
- C Pull out some paper outside the printer and then close the printer cover.
- D Close the top cover. Press the printer cover to avoid error position of roll paper.
- E Tear-off the paper correctly.

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best

together we quest for the best.

