

OCPP-M082 Hochwertige 80mm usb mobile Handheld-Bluetooth-Drucker

(Modell: OCPP-M082)

Eigenschaften:

- 1.Support von Windows, Java, Android oder IOS.
- 2.Bluetooth, USB und RS232 Kommunikation für Wahl.
- 3.Battery Ladeanzeige, einfach zu wissen, Rest Macht.
- 4.Higher Druckgeschwindigkeit 90mm / sek.
- 5.100km TPH Leben.
- 6.Low Stromverbrauch und hoher Kapazität Lithium-Batterie

Spezifikation:

| | |
|-----------------------------------|---|
| Insgesamt Abmessungen (B × T × H) | 98 × 103 × 45 mm |
| Gewicht | 280g |
| Farbe | Schwarz |
| Effektive Druckbreite | 72mm |
| Druckverfahren | Thermisches Zeilendruck |
| Druckbefehle | ESC / POS-Befehlssatz kompatibel |
| Druckgeschwindigkeit | Bis zu 90 mm / s |
| Lösung | 8 Punkte / mm (203 dpi) |
| drucken Schrift | 12x24 / 24x24 |
| Säulenkapazität | 32 Spalten / 16columns |
| Schriftgröße | 1,5 x 3,0 mm (B x H) / 3.0x3.0mm (BxH) |
| Papierabmessungen | 80,0 ± 0,1 mm x Durchmesser 30.0mm |
| Papierstärke | 0,06 bis 0,08 mm |
| Zeichensatz | Alphanumeric / Chinese Kanji |
| Schnittstelle | USB, RS-232, Bluetooth (optional) |
| Datenpuffer | Bis zu 5 K Bytes |
| Netzteil | 9V DC / 2A |
| Battery Power | 7,4V DC / 2000 mA; Batterie kann durch für 4-5 Tage zu bleiben, wenn es die volle Leistung ist, kann es 120-150m Papier drucken |
| Andere Eigenschaften | Papiererkennung, Stromerkennung, manuelle Abschaltung |
| Arbeitsbedingungen | Temperatur: -10 °C ~ 50 °C, Feuchtigkeit: 10% ~ 90% |
| Lagerbedingungen | Temperatur: -20 °C ~ 70 °C, Feuchtigkeit: 5% ~ 95% |
| Gerätename | besonders angefertigt, Schreiben und digital für Option sein kann, auf maximal 30 ASCII-Zeichen. |
| Passwort | Geben Sie Standard-Pairing-Code "1234", kann es angepasst werden. Bei max 6 digitals. |
| Netzstecker Dimension | 3.5 * 1.1mm |
| Details direkt | |

Produktabbildung:



**80mm Bluetooth
Thermal Receipt Printer
for Andriod or IOS
OCPP-M082**



Product Picture





Features

Simple but not easy

Support Windows, Android,
or iPhone OS;



Bluetooth, USB and
RS232 communication.

Battery charge indicator, easy to know rest power.



Higher print speed 90mm/sec.

100km TPH Life.



Mini Thermal Printer
Model: OCPP-M602
Printing Speed: 90mm/s
Paper Width: 80mm
Power Supply: 5V1.5A
Interface: USB A/B/3.2
43070003



Low power consumption
and large capacity
Lithium battery.



All-round show





Application Area

Bus/Taxi receipt, Traffic Citation, Logistics, Transportation, Warehouse management, Delivery, Illegal Parking Ticket, Drugstore, Food delivery, restaurant, Price Tag, Retail/Farm

Delivery



Restaurant



Bus / Taxi Receipt



Traffic Citation



| | |
|----------------------------------|--|
| Overall Dimension (W×D×H) | 98×103×45mm |
| Weight | 280g |
| Color | Black |
| Effective print width | 72mm |
| Print method | Thermal line printing |
| Print commands | ESC/POS/STAR compatible command set |
| Print speed | Up to 90mm/sec |
| Resolution | 8 dots/mm(203dpi) |
| Print font | 12x24/ 24x24 |
| Column capacity | 48 columns/24 columns |
| Character size | 1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(W x H) |
| Paper dimensions | 80.0±0.1mm x diameter 30.0mm |
| Paper thickness | 0.06 to 0.08mm |
| Character set | Alphanumeric/ Chinese Kanji ASCII Font A:12×24 Font B: 9x17 Korean code page 949 |
| Communication Interface | USB/RS-232, Bluetooth |
| Flash | 256KB |
| Power Adapter | 9V DC/1.5A |
| Battery Power | 7.4V DC/ 2000mA; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paper |
| Other features | Paper detection, power detection, Manual shut down |
| | Temperature:-10 degC ~ 50 degC Humidity:10% ~ |

| | |
|----------------------|---|
| Working conditions | Temperature: 0 degC ~ 40 degC, Humidity: 5% ~ 90% |
| Storage conditions | Temperature: -20 degC ~ 70 degC, Humidity: 5% ~ 95% |
| Device name | Can be customized, letter and digital for option, at max 30 ASCII characters. |
| Password | Enter default pairing code "1234", it can be customized. At max 6 digitals. |
| Power plug dimension | 3.5*1.1mm |

Paper Roll Installation



- A Open the printer cover.
- B Install the roller in the roll paper, and put them into the printer.
- C Pull out some paper outside the printer and then close the printer cover.
- D Close the top cover. Press the printer cover to avoid error position of roll paper.
- E Tear-off the paper correctly.

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best

together we quest for the best.

