

# 15.1 Inch Aluminium Alloy Touch POS Terminal

(M/N: POS -1513W& POS -1513A)



OCOM 1513 series POS terminal has aluminium alloy shell and base. It has Intel Celeron and Intel Core I series CPU for option. It is easy to install 2<sup>nd</sup> display, MSR, VFD as modules. This model is very convenient for maintenance by removing the back cover and it has rich I/O interfaces to be connected to more external devices.

## **Merkmale:**

- I Intel Celeron series and Intel Core I3 I5 processor for option
- I Rockchip high speed RK3288 processor for option
- I EMMC 8GB/16GB/32GB for option
- I Hard Drive M.2 SSD 64GB, SSD 128GB and 256 GB for option
- I Multi-point projected capacitive touch panel
- I Optional side MSR and VFD220 customer display mounted to back cover
- I True flat and water-proof scratch-resistant surface display

## **Spezifikationen:**

Modell	POS -1513W	POS -1513A
Name	15.1 inch aluminium alloy touch POS terminal	
Gehäuse	aluminium alloy shell machine body and base	
Farbe	whole black color machine	
Anzeige		
Hauptbildschirm	15.1 inch touch screen monitor	
Resoluiton	1024*768	
Helligkeit	250cd/m <sup>2</sup> .	
View angle	Horizon: 160; Vertical :150	
Touch-Screen	Multi-point projected G+G capacitive touch	
Sub-display	9.7 inch display W/o touch function	
Customer display	2*20 VFD or 2*20 LCD display mounted to back cover for option	
Leistung		
Hauptplatine	Intel Celeron Bay Trail J1900 2.0GHz usually or intel core I3 / I5 4 <sup>th</sup> generation CPU for option	Rockchip series RK3288 ,quad core 1.8G, RK3399 for option
Systemspeicher	1*SO-DIMM DDRIII slot, support1333*/1600 4GB usually ,2GB/8GB for option	On board DDRIII 1GB,2GB,4GB for option
Speichermedium	Msata SSD 64GB or higer, up to 256GB	on board8GB,16GB ,32GB EMMC for option
Audio	On board Real Tek ALC662	on board Real Tek ALC5640 audio chip
LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module	10/100Mbs,Realtek RTL8111F Lan chip□Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support
Betriebssystem	Windows7/8/10, Embedded,WE POS ,Linux	Up to Android 8.1
Connectivity		

External I/O port(J1900/RK3288)	power button*1
	12V DC in jack*1
	LAN:RJ-45*1
	USB*4
External I/O port J1900	15PIN D-sub VGA *1
	HDMI*1 or RS 232*1 for option
	line out*1,MIC in*1
External I/O port RK3288	Audio out*1
	TF card port*1
	RJ11 for cash drawer*1
	RS 232*1
Optionen	
MSR	optional side MSR
Umfeld	
Betriebstemperatur	0 to 40 degrees centigrade
Lagertemperatur	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Paket	
Gewicht	Net 5.5Kg, Gross 7.0Kg
Package with foam inside	440*290*425mm
Zubehör	
Netzteil	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor
Stromkabel	Power cable plug compatible with USA /EU / UK etc and customized available
Sonstiges	
Konformität	FCC Class A/CE Mark/LVD/CCC