## TM-1106 1366x768 HDMI wasserdichter industrieller 12 Zoll USB LCD pos Touch Monitor

**(M / N: TM-1106)**

### Eigenschaften:

Hohe Auflösung: Unterstützung 1366 * 768;
Mehrpunkt Kapazitiv Berühren Sie Bedienfeld;
VGA-Anschluss und VGA-Kabel für Standard;
Eingebautes HDMI-Anschlusskabel für optionales Zubehör;
Lebensdauer: 5 Millionen Berührung;
Stabile Basis zum Einstellen des Bildschirmhöhenwinkels.

### Spezifikation:

| | |
|---|---|
| LCD-Bildschirmgröße | 11.6" |
| Seitenverhältnis | 16: 9 |
| Auflösung | 1366 * 768 |
| Pixelabstand (mm) | 0,297 |
| Anzahl der Farben | 16,2 Millionen |
| Kontrastverhältnis | 700/1 |
| Helligkeit | 400 cd / m² |
| Reaktionszeit | 8ms |
| Touch-Panel | 11.6" Mehrpunkt Kapazitiv Berühren Sie Bedienfeld |
| Schnittstelle | VGA für Monitor, USB für Touchscreen, HDMI-Kabel für Optional |
| Leistung | 12 V DC 3A |
| Betriebstemperatur | -10C ~ 60C |
| Härtetest schlägt zu | Über 10 Millionen |
| Linearität | 1,50% |
| Schichtdicke | 0,175 mm, 0,188 mm |

Aocom®
At your side

# TM-1106

ISO FC CE RoHS

Aocom®
At your side
TM-1106
ISO
FC
CE
RoHS

Aocom®
At your side
TM-1106
300°
ISO
FC
CE
RoHS

Aocom®
At your side

# TM-1106

ISO FC CE RoHS

Aocom®
At your side

# TM-1106

ISO FC CE RoHS

Aocom®
At your side
TM-1106
ISO
FC
CE
RoHS

Aocom®
At your side
TM-1106
ISO
FC
CE
RoHS

Aocom®
At your side

# TM-1106

ISO FC CE RoHS

Aocom®
At your side

# TM-1106

ISO FC CE RoHS

Aocom®
At your side

# TM-1106

ISO FC CE RoHS

Aocom®
At your side

# TM-1106

ISO FC CE RoHS