## Drahtloser 24-GHz-Laser-Barcode-Scanner

(Modell: OCBS-W600)

#### **SPEZIFIKATION::**

SPEZIFIKATION		
PHYSIKALISCHE EIGENSCHAFT	ΓEN	
Lichtquelle:	Sichtbare Laserdiode (VLD) bei 650 nm-670 nm	
Scannerabmessungen:	164 mm * 67 mm * 95 mm(B * H * T)	
Empfängerabmessungen:	130 mm * 45 mm * 129 mm(B * H * T)	
Material:	ABS + TPR / Aluminiumlegierung	
Gewicht:	235 g	
Scanmodus:	Handheld; bidirektionaler Scanmodus.	
Kontrollleuchte:	LED rot und blau	
Summer:	Summerlautstärke einstellbar	
LEISTUNGSMERKMALE		
Breite des Scanfeldes:	60 mm @ 30 mm∏□Von der Motorfläche∏	
	98 mm @ 100 mm∏von der Motorfläche∏	
Tiefe des Scanfeldes:	2,5-600 mm∏∏Kontrast 0,9 Dichte 0,25∏	
Scan-Geschwindigkeit:	100 Scans / Sek	
Scan-Präzision:	0,10 mm[]4mil[] PCS0.9	
Bit Fehlerrate:	1 / (5 Millionen)	
	UPC / EAN, UPC / EAN mit Ergänzungen, UCC / EAN128,	
	Code39, Code 39, Voll-ASCII, Trioptic-Code 39, Code 128,	
Dekodierungsfähigkeit:	Code 128, Voll-ASCII, Codabar, Interleaved 2 von 5, Discrete	
	2 von 5, Code 93, MSI, Code 11, RSS-Varianten, Chinesisch 2	
	von 5	
Batterie:	3,7 V / 750 mAh, Li-lon	
Aufladezeit:	3,0 Stunden	
Scan Zeit:	30 Stunden	
Aktuell:	100 mA (arbeiten); 40mA (Standby)	
Winkel:	Steigung: 60 °; Neigung: 45 °	
Kommunikationsentfernung:	30m	
Arbeitsfrequenz:	2,4G	
Erinnerung	16 MB	
Kommunikationsinterface:	USB	
BENUTZERUMGEBUNGSEIGEN	ISCHAFTEN	
	0Grad C. bis 50Grad C. (Betriebs), -40Grad C.bis 70 Grad C.	
Temperatur:	(Lager)	
Relative Luftfeuchtigkeit:	5% -90% (nicht kondensierend)	
	Hält wiederholten Stürzen von 1,5 m auf die	
Drop-Spezifikation:	Betonoberfläche stand	
Umgebungsbeleuchtung:	0 ~ 100.000 LUX	
Elektrostatische Entladung:	Entspricht $\pm 12$ KV Luftaustritt und $\pm 6$ kV Kontaktentladung	
Sicherheitszertifikat:	CE, FCC, Klasse 2, RoHS	
·		

Produktdetails:



# Product Picture



ocomin









minc.com

-ominc.com

# All-round show









# Parameter

mine	ocominc.eo	
PHYSICAL CHARACTERSTICS	Visible Laser Diode (VLD) @ 650 nm-670nm	b,
Light Source	Visible Laser Diode (VLD) @ 650 nm-670nm	
Scanner Dimensions(W * H * D)	164mm * 67mm * 95mm	
Receiver Dimensions(W * H * D)	130mm*45mm*129mm	
Material	ABS+TPR /Aluminium alloy	
Weight	235g	
Scanning Mode	Hand-held; bidirectional Scanning Mode.	
Indicator Light	LED Red and Blue	
Buzzer	Buzzer Volume Adjustable	
PERFORMANCE CHARACTERSTICS	yb va	
Width of Scan Field	60mm@30mm (From engine face) 98mm@100mm (from engine face)	
Depth of Scan Field	2.5-600mm (Contrast 0.9 Density 0.25)	
Scan Speed - 0	100 scans/sec	21
Scan Precision	0.10mm (4mil) PCS0.9	
Bit Error Rate	1/(5million)	
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5	
Battery	3.7V/750mAh,Li-ion	
Charge Time	3.0 Hours	
Scan Time	30 Hours	
Current	100mA (working); 40mA(standby)	
and the second		

Angles	Pitch:60°; Tilt: 45°
Communication Distance	30m
Memory	2.46
Communication Interface	USB,RS232,PS2
USER ENVIRONMENT CHARACTER	STICS OCC
Temperature	0°C to 50°C (Operating), -40°C to 70°C (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

# Shipping and payment

- 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
- EXPRESS: around 3-7 working days to arrive
- nimoso, www. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which 3. destination port
- By sea: depend on which destination port 4.
- 5.
- 6. Western Union
- 7. Escrow
- L/C

### Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.





We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.











wocomin



#### Relevante Dokumente:

**Spezifikation**