supermarkt mini usb 2d laser barcode scanner

(Modell: OCBS -2008)

Hochleistungs-Imaging-Technologie;
Omnidirektionales Scannen, einfach zu scannen;
Kann den Barcode auf dem Bildschirm und den Farbcode lesen.
4mil ausgezeichnete Scangenauigkeit;
Multi-Sonderfunktionseinstellung unterstützt;
Multi Schnittstellen optional;
Für Option stehen.

Leistungsmerkmale

Funktion		
Lichtquelle		Weiße LED
Signalton		Unterstützt
Stand		Wahlweise
Indikator		Grüne LED, Piepton
Leistung scannen		
Sensor		CMOS
Auflösung		640 * 480,256 Graustufen
Maximale Dekodiergeschwindigkeit		13mil UPC 40 cm / s
Lesewinkel		horizontal 50 Grad; vertikal 20 Grad
Präzision		≥4mil
Decodierungsfähigkeit	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39, vollständiger ASCII-Code, Code 32, Trioptic-Code 39, Interleaved 2 von 5, Industrial 2 von 5 (diskret 2 von 5), Matrix 2 von 5, Codabar (NW7), Code 128, UCC / EAN 128 (GS1-128), ISBT 128, Code93, Code 11 (USD-8), MSI / Plessey
	2D	PDF417, MicroPDF417, QR-Code, DataMatrix, Han Xin-Code, Aztec-Code, GS1 Com pos ite
Tiefenschärfe		Code 39 (5mil): 50 mm ~ 120 mm Code 39 (10 mil): 25 mm ~ 250 mm UPC / EAN (13mil) 20mm ~ 320mm Datenmatrix (7,5 mil): 63 mm ~ 150 mm PDF417 (6.6mil): 62mm ~ 145mm
Empfindlichkeit		Neigung ± 45 ° @ 0 ° Rolle und 0 ° Neigung Drehung ± 30 ° bei 0 ° Neigung und 0 ° Neigung Durchbiegung ± 45 ° @ 0 ° Roll und 0 ° Neigung
Elektrisch		
Schnittstelle		USB, USB COM (virtuelle serielle Schnittstelle)
Eingangsspannung		3,3 V ~ 5 V DC
Standardleistung		2,0 w (400 mA)
Maximale Kraft		2.5w (450mA)
Gleichstromadapter		Max. 5,5 V 1A
LED-KLASSE		Klasse I
EMV-Test		FCC part15, IEC60825-1, EN55022 Klasse B
Benutzerumgebung		
Temperatur betreiben		-20 ° C ~ +60 ° C (-4 ° F bis 144 ° F)
Lagertemperatur		-30 ° C ~ +70 ° C (-22 ° F bis 158 ° F)
Feuchtigkeit		5% - 95% (nicht kondensierend)
Fallschutz:		1,5 m fällt auf Beton
IP-Klasse		IP54
Lichtintensität		Arbeiten: Sonnenlicht, Leuchtstofflampen
Physisch		
Maße		156 * 68 * 83 mm
Gewicht		195 g (ohne Ständer)
Paket dimension		48 * 36 * 47cm (20 Stück mit Standfuß 13,5kg)
		48 * 39 * 52cm (30 stücke ohne stand 15kg)

Handheld Image Scanner for1D/2D Barcode

OCBS-2008

Product Picture

Features

Reliable with good price

High performance imaging technology;
Omni-directional scanning, easy to scan;

4mil excellent scanning accuracy ;
Can read the barcode on the screen and color barcode;

Multi special function setting supported;
SDK/API Available;

Multi interfaces optional;
Stand for option.

Application place

Bookstore

Supermakte

Pharmacy

Warehouse

Restaurant

Clothing store

Parameter

Function		
Light source		White LED
Beep		Supported
Stand		Optional
Indicator		Green LED, beep
Scan performance		
Sensor		CMOS
Resolution		640*480,256 gray levels
Maximum decoding speed		13mil UPC 40cm/s
Reading angle		horizontally 50 deg; vertically 20 Deg
Precision		≥4mil
Decode capability	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128 (GS1-128), ISBT 128, Code93, Code 11 (USD-8), MSI/Plessey
	2D	PDF417, MicroPDF417, QR Code, DataMatrix, Han Xin Code, Aztec Code, GS1 Composite
Depth of field		Code 39(5mil)：50mm~120mm Code 39(10mil)：25mm~250mm UPC/EAN (13mil)：20mm~320mm Data Matrix(7.5mil)：63mm~150mm PDF417(6.6mil)：62mm~145mm
Sensitivity		Inclination ±45° @0°Roll and 0°Skew Rotation ±30° @0°Pitch and 0°Skew Deflection ±45° @0°Roll and 0°Skew
Electrical		
Interface		USB,USB COM(virtual serial port)
Input Voltage		3.3v~5v DC
Standard Power		2.0w (400mA)
Max Power		2.5w (450mA)
DC adapter		Max 5.5V 1A
LED CLASS		Class I
EMC Test		FCC part15,IEC60825-1,EN55022 Class B
User Environment		
Operate Temperature		-20 deg C ~ +60 deg C (-4 Deg F to 144 deg F)
Storage Temperature		-30 deg C ~ +70 Deg C (-22 Deg F to 158 deg F)
Humidity		5% - 95%(non- condensation)
Drop resistance:		1.5m (5.0ft) drops to concrete
IP class		IP54
Light intensity		Working: sun lights, fluorescent lights
Physical		
Dimensions		156*68*83mm
Weight		195 g (without stand)
Package dimension		48*36*47CM (20pcs with stand 13.5KG)
		48*39*52CM (30pcs without stand 15KG)

Production Capacity:

✓ Indicates information has been verified onsite by a certification specialist

Production Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

Verified by TUV on 2013.7.15

Quality Assurance:

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.
Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services.
OCOM's products have passed CE, FCC, TUV, RoHs and other certifications.
We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments:

✓ Indicates information has been verified onsite by a certification specialist

Test Equipment and Facilities

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

Verified by TUV on 2013.7.15

Certification:

Warranty and After Sales:

- All products' warranty are not less than 12 month, some models even up to 24 months warranty.
- Spare parts will be provided for mass orders for customers' local maintenance.
- Any product found to be defective within 30 days of shipment shall be deemed Dead on Arrival (DOA). DOA products will be advance replaced and shipped via express.
- Have distributors or authorized agents in the main market who can provide local repair and replacement services.
- Professional CRM management insures fast respond for customer's enquiries and orders tracking.
- Sales with many years experience in foreign trade, proficient in foreign languages and strong sense of responsibility.
- 7*24 hours online, responds with 12 hours in working days, and within 24 hours for rest days.

Packing and Shipment:



Payment:

Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have estabilshed goods relationship with our customers and have friendly communication with each other.

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers , Thermal Printer, Barcode printer,Dot Matrix Printer、Barcode Scanner, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.

FAQ

1. Gewährleistung
OCOM ist darauf ausgerichtet, die kostengünstigsten Produkte und Dienstleistungen mit höchster Qualität anzubieten, die die Zufriedenheit der Kunden erfüllen. Unsere Garantie für die Produkte beträgt normalerweise 12 Monate ab dem Versand. Einige der angegebenen Modelle können eine Garantie von 24 Monaten haben. Bei Massenbestellungen können wir Ihnen einige Ersatzteile für die Reparatur vor Ort liefern. Danach können Sie defekte Teile zur Nacharbeit zurücksenden.

2. Zahlungsbedingungen
Für Massenbestellungen können Sie uns bezahlen, indem Sie T / T, LC, Western Union, Escrow oder andere verwenden. Über Probenauftrag, T / T, Western Union, Übertragungsurkunde, Paypal sind annehmbar. Der Treuhandservice wird von Alipay.com bereitgestellt. Derzeit können Sie mit Moneybookers, Visa, MasterCard und Banküberweisung bezahlen. Sie können auch mit ausgewählten Debitkarten wie Maestro, Solo, Carte Bleue, Pos tePay, CartaSi, 4B und Euro6000 bezahlen.

3. Versand
Wir akzeptieren alle Arten von Versandarten, einschließlich: Express, Luft, Meer, Auto oder Abholung durch Kunden persönlich.

4. Probenverfügbarkeit & Politik
Nachdem die Kunden unsere Spezifikation bestätigt haben, freuen wir uns, Muster zur Prüfung und Qualifizierung zur Verfügung zu stellen. Alle Proben sollten vor dem Versand bezahlt werden, und der Preis der Proben ist etwas höher als die Massenbestellung. Wenn die Massenbestellung aufgegeben wurde, können wir Ihnen die Kosten für die Muster zurücksenden oder Ihnen weitere Produkte mit den Versandstücken zusenden. Sie können die Muster bei uns direkt mit t / t, Western Union oder paypal kaufen. Und Sie können es auch in unserem Online-Shop bei aliexpress kaufen:
http://www.aliexpress.com/store/403448?tracelog=minisite_CI Die Musterbestellung wird benötigt, bevor wir unseren factie freigeben

5. Kundendienst:
*** Wir haben die oberste 1% ige Handelsversicherung bis zu USD12000, die von Alibaba garantiert wird, die Ihr Geld gut schützen kann, um die Lieferzeit und die Produktqualität sicherzustellen. (1) Die Garantie für alle Produkte beträgt mindestens ein Jahr, einige Modelle sogar eine Garantie von bis zu zwei Jahren. (2) Ersatzteile für Massenaufträge für die lokale Wartung der Kunden werden zur Verfügung gestellt. (3) Vertriebspartner oder autorisierte Vertreter auf dem Hauptmarkt haben, die lokale Reparatur- und Austauschdienste erbringen können. (4) Ein professionelles CRM-Management gewährleistet eine schnelle Kundenanfrage und Auftragsverfolgung. (5) Vertrieb mit langjähriger Erfahrung im Außenhandel, Fremdsprachenkenntnissen und Verantwortungsbewusstsein. (6) 7 ***

24 Stunden online, Arbeitstage antworten innerhalb von vier Stunden, Ruhetage innerhalb von 12 Stunden.

6. Herunterladen
Sie können auf http: // www zugreifen. pos solution.com.cn/cn/download.html downloadet Treiber, SDK-Software, Produktspezifikationen und Benutzerhandbücher.

7. Video Guide
Um Kunden dabei zu unterstützen, unsere Produkte besser zu nutzen, haben wir Video-Anleitungen aufgenommen und hochgeladen. Sie finden sie unter http: // www. pos solution.com.cn/video.html.

8. MOQ-Richtlinie
Keine MOQ-Einschränkung für die Standardprodukte, aber der Preis pro Einheit ist unterschiedlich. Für eine kundenspezifische Produktion können Sie das MOQ mit unserem Vertriebsmitarbeiter besprechen.