

**100scans / s USB automáticamente escáner de código de barras láser de exploración
(Modelo: OCBS-LA06)**

Especificaciones del producto:

Características	
Fuente:	Láser visible (650-670nm)
Velocidad de escaneo:	100 lecturas por segundo
Distancia de lectura	2.5 ~ 600 mm (100% UPC / EAN)
Tipo de digitalización:	Bidireccional
Resolución:	0,10 mm (4mil) en PCS 0.9
Contraste de impresión baja:	20%, la diferencia mínima de reflectancia (@ 650nm en)
Capacidades de decodificación:	UPC / EAN, UPC / EAN con suplementos con, UCC / EAN 128, código 39, código 39 ASCII completo, código 39 TriOptic, código 128, código 128 ASCII completo, codabar, Interleaved 2 de 5, discreto 2 de 5, Código 93, MSI , código 11, ATA, variantes de RSS, chinos 2 de 5 ...
Características físicas	
Interfaces compatibles:	PS2, RS232, USB
Voltaje:	DC + 5V +/- 5%
El trabajo actual:	100 mA
Corriente sin carga:	& Amp; Lt; 40 □□
Fuente de alimentación:	Anfitrión (RS232) de alimentación externa de energía o
Ángulo de la exploración	Ángulo de elevación de 45 ° a 60 °
Dimensiones:	Punto L165.42mm punto ¯xW69.72mm ¯xH89.67mm
Peso:	140 g (excluyendo el soporte de montaje)
Soporte	Se suministra con
Color:	Marfil o Negro
Entorno de usuario	
Temperatura de trabajo:	0-50 degre eC
Temperatura de almacenamiento:	-40 ~ 70degreeç
Humedad:	5 ~ 95% de humedad relativa, sin condensación
Descarga electrostática:	Confirmar a ± 15 kV descarga de aire y + 8KV de descarga por contacto
Caída especificaciones de resistencia:	El concreto puede soportar múltiples prueba de caída de 1,5 m
Seguridad:	
EMI / RFI:	FCC Clase A y CE
Seguridad del láser:	CDRH productos 2 láser

Detalles del producto:



*Handheld Laser
Barcode Scanner*

OCBS-LA06

Product Picture





Features

Simple but not easy

Auto-Induction built in, green design



High scan rate and long reading



distance



Excellent decode capability



KBW, RS232 and USB supported

Durable construction combined with future-proofing



|| All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
Physical Characteristics	

Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	With
Color:	Ivory and black
User Environment	
Operating Temperature:	0°C~50°C
Storage Temperature:	-40°C~ 70°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.

