

## **Escáner de código de barras inalámbrico de mano 1D Bluetooth para el sistema pos**

**Modelo No: OCBS -W600**

### **Característica:**

escáner de código de barras, escáner de código de barras inalámbrico, escáner de código de barras de mano

Escáner de código de barras láser inalámbrico 2.4 G

Velocidad de escaneo: 100scans / sec

Distancia de transmisión de datos alcanza 30min área abierta;

Tiempo de escaneo: 30 horas







Scan speed: 1000000000

Data transmission distance reaches  
30m in open area;



Scan Time:30hours



## ||| All-round show





## Parameter

| PHYSICAL CHARACTERISTICS       |                                                                                                                                                                                                                                 |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Light Source                   | Visible Laser Diode (VLD) @ 650 nm-670nm                                                                                                                                                                                        |
| Scanner Dimensions(W * H * D)  | 164mm * 67mm * 95mm                                                                                                                                                                                                             |
| Receiver Dimensions(W * H * D) | 130mm*45mm*129mm                                                                                                                                                                                                                |
| Material                       | ABS+TPR /Aluminium alloy                                                                                                                                                                                                        |
| Weight                         | 235g                                                                                                                                                                                                                            |
| Scanning Mode                  | Hand-held; bidirectional Scanning Mode.                                                                                                                                                                                         |
| Indicator Light                | LED Red and Blue                                                                                                                                                                                                                |
| Buzzer                         | Buzzer Volume Adjustable                                                                                                                                                                                                        |
| PERFORMANCE CHARACTERISTICS    |                                                                                                                                                                                                                                 |
| Width of Scan Field            | 60mm@30mm (From engine face)<br>98mm@100mm (from engine face)                                                                                                                                                                   |
| Depth of Scan Field            | 2.5-600mm (Contrast 0.9 Density 0.25)                                                                                                                                                                                           |
| Scan Speed                     | 100 scans/sec                                                                                                                                                                                                                   |
| Scan Precision                 | 0.10mm (4mil) PCS0.9                                                                                                                                                                                                            |
| Bit Error Rate                 | 1/(5million)                                                                                                                                                                                                                    |
| Decode Capability              | UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5 |
| Battery                        | 3.7V/750mAh,Li-ion                                                                                                                                                                                                              |
| Charge Time                    | 3.0 Hours                                                                                                                                                                                                                       |
| Scan Time                      | 30 Hours                                                                                                                                                                                                                        |
| Current                        | 100mA (working); 40mA(standby)                                                                                                                                                                                                  |

|                                         |                                                               |
|-----------------------------------------|---------------------------------------------------------------|
| Angles                                  | Pitch:60°; Tilt: 45°                                          |
| Communication Distance                  | 30m                                                           |
| Memory                                  | 2.4G                                                          |
| Communication Interface                 | USB ,RS232,PS2                                                |
| <b>USER ENVIRONMENT CHARACTERISTICS</b> |                                                               |
| Temperature                             | 0℃ to 50℃ (Operating), -40℃ to 70℃ (Storage)                  |
| Relative Humidity                       | 5%-90%(Non-Condensing)                                        |
| Drop Specification                      | Withstands repeated 1.5m drops to concrete surface            |
| Ambient Illumination                    | 0~100,000 LUX                                                 |
| Electrostatic Discharge                 | Conforms to ±12KV air discharge and ±6KV of contact discharge |
| Safety Certificate                      | CE, FCC, Class 2, RoHS                                        |

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.





We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com),  
Together we quest for the best.

