80mm Auto Cortador POS Impresora térmica de recibos
(Modelo: OCPP-806)

Pliego de condiciones:

Método de impresión	Térmica directa
Impresión de caracteres	576 puntos / línea, 512 puntos / línea, caracteres ANK
Fuente	A: 12 * 24dots, 1.5 (W) * 3.0 (H) mm; B: 9 * 17dots, 1.1 (W) * 2.1 (H) mm
Simplificado / Chino tradicional	24 * 24dots, 3.0 (W) * 3.0 (H) mm
Tipo de código de barras	UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) CODABAR / ITF / CODE39 / CODE93 / CODE128
Velocidad de impresión	300 mm / seg
Interfaz	Serial + USB + Ethernet
Comando de Impresión	Compatible con ESC / POS
Drivers	Win9X / Win2000 // Win2003 / Win Vista / Win 7 / Windows XP /, compatible con ESPON
Ancho de impresión	79,5 ± 0,5 mm (ancho de impresión de 72 mm)
Diámetro de papel	83mm
Grosor del papel	0.06-0.08mm
Cortador	Cortador automático
Fiabilidad de impresión	100 kilometros
Potencia	DC24V / 2.5A
Temperatura	0-45 grados
Contraste Humedad	10-80%
Dimensión externa	195d * 155W * 148H mm
Peso bruto	2,70 kg
Paquete	Caja interior: 29 * 21 * 17cm; Tamaño de la caja (8 piezas): 60 * 44 * 36 (cm)

Detalles del producto:

Product Picture

Features

Simple but not easy

Water-proof and grease-proof.

Support NV image downloading and printing
Support different density bitmap graphics printing

Support raster bitmap printing

USB+Serial +Ethernet

High Printing Speed
(Max 260mm/second)
Auto Cutter Optional

Characters can be amplified, printed in bold optionally, and line spacing printing can be adjusted

All-round show

Application Area

Food delivery, restaurant, Traffic Citation, Logistics, Transportation, Warehouse management, Delivery, Illegal Parking Ticket, Drugstore, Price Tag, Retail/Farm

Paper Roll Installation

A Open the printer cover.

B Install the roller in the roll paper, and put them into the printer.

C Pull out some paper outside the printer and then close the printer cover.

D Close the top cover. Press the printer cover to avoid error position of roll paper.

E Tear-off the paper correctly.

Setting the Printing Mode(DIP switches):

The DIP switches are used to set the printer to perform various functions, such as cutter mode, character set, speed, beeper, print density and etc.

Parameter

Printing Method	Direct Thermal
Printing Character	576 dots/line, 512 dots/line, ANK characters
Font	A: 12*24dots,1.5(W)*3.0(H)mm; B: 9*17dots,1.1(W)*2.1(H)mm
Simplified/Traditional Chinese	24*24dots, 3.0(W)*3.0(H)mm
Barcode Type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODABAR/ITF/CODE39/CODE93/CODE128
Printing Speed	300mm/sec
Interface	Parallel or Serial + USB + Ethernet
Printing Command	Compatible with ESC/POS
Drivers	Win9X/Win2000//Win2003/Win Vista/ Win 7/Window XP /, compatible with ESPON, SAMSUNG
Printing Width	79.5±0.5mm(print width 72mm)
Paper Diameter	83mm
Paper Thickness	0.06-0.08mm
Cutter	Auto cutter
Printing Reliability	100km
Power	DC24V/2.5A
Temperature	0-45 degree
Contrast Humidity	10-80%
External Dimension	195D*155W*148H mm
Gross Weight	2.70kg
Package	Inner Box: 29*21*17cm; Carton Size (8 pcs): 60*44*36(cm)



Connection







a. Plug the DC cord connector into the printer's power connector..
b. Plug the data cable connector into the printer's interface connector.
C. Plug the drawer cable into the drawer kick-out connector on the back of the printer next to the interface connector.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocomtinc.com