Impresora térmica móvil 80mm Android IOS Bluetooth Pos (Modelo: OCPP-M082)

Presupuesto:

Dimensiones (W × D × H)	98 × 103 × 45 mm
Peso	280 g
Color	Negro
Ancho de impresión efectivo	72 mm
Metodo de impresion	Impresión térmica de líneas
Comando de impresión	Conjunto de instrucciones compatible con ESC / POS
Velocidad de impresión	A 90mm / sec
Resolución	8 puntos / mm (203DPI)
Imprimir fuente	En 12X24 / 24x24 en
Capacidad de columna	48/24 columnas
Tamaño del personaje	1.5 × 3.0 mm (ancho x alto) / 3.0x3.0mm (ancho x alto)
Tamaño de papel	Diámetro de 80.0 mm a ± 0.1mm x30.0
Grosor del papel	0.06 a 0.08 mm
Conjunto de caracteres	Texto alfanumérico / chino
Interfaz	USB, RS-232, Bluetooth (opcional)
Destello	256KB
Adaptador de corriente	9V DC / 2A
Energía de la batería	DC / 2000 mA 7.4V; la batería puede permanecer en 4-5 días, cuando está llena de fuerza, puede imprimir en papel de 120-150M
Otras características	Detección de papel, detección de potencia, apagado manual.
Las condiciones de trabajo	Temperatura: -10grado C~50grado CHumedad: 10%~90%
Condiciones de almacenaje	Temperatura: -20grado C~70 grado C

Detalles del producto:

Product Picture

Features

Simple but not easy

Support Windows, Android, or iPhone OS;

Bluetooth, USB and RS232 communication.

Battery charge indicator, easy to know rest power.
Higher print speed 90mm/sec.
100km TPH Life.

All-round show

Application Area

Bus/Taxi receipt, Traffic Citation, Logistics, Transportation, Warehouse management, Delivery, Illegal Parking Ticket, Drugstore, Food delivery, restaurant, Price Tag, Retail/Farm

Delivery

Restaurant

Bus / Taxi Receipt

Traffic Citation

Overall Dimension (W×D×H)	98×103×45mm
Weight	280g
Color	Black
Effective print width	72mm
Print method	Thermal line printing
Print commands	ESC/POS/STAR compatible command set
Print speed	Up to 90mm/sec
Resolution	8 dots/mm(203dpi)
Print font	12x24/ 24x24
Column capacity	48 columns/24 columns
Character size	1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(W x H)
Paper dimensions	80.0±0.1mm x diameter 30.0mm
Paper thickness	0.06 to 0.08mm
Character set	Alphanumeric/ Chinese Kanji ASCII Font A:12×24 Font B: 9x17 Korean code page 949
Communication Interface	USB/RS-232, Bluetooth
Flash	256KB
Power Adapter	9V DC/1.5A
Battery Power	7.4V DC/ 2000mA; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paper
Other features	Paper detection, power detection, Manual shut down
	Temperature:-10 degC～50 degC Humidity:10%～

Working conditions	90%
Storage conditions	Temperature:-20 degC ~ 70 degC,Humidity:5% ~ 95%
Device name	Can be customized, letter and digital for option, at max 30 ASCII characters.
Password	Enter default pairing code "1234", it can be customized. At max 6 digitals.
Power plug dimension	3.5*1.1mm

Paper Roll Installation

A Open the printer cover.

B Install the roller in the roll paper, and put them into the printer.

C Pull out some paper outside the printer and then close the printer cover.

D Close the top cover. Press the printer cover to avoid error position of roll paper.

E Tear-off the paper correctly.

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.
OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.
OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.
You can find more information of us at: www.ocominc.com,
Together we quest for the best.

Documentos importantes:

¿Quieres saber más inf del producto?ormación?Por favor Haga clic aquí.

***Especificacionion**

***Manual del programa**

***Manual de instrucciones**

***Driver para Windows**

***Herramientas de configuración de parámetros de impresora**

***USB PrintDemo(Demo de software de aplicación)**

***Bluetooth PrintDemo(Demo de software de aplicación)**

***SDK para Android**

***discos compactos Archivos**