

# Escáner portátil del código de barras del laser del sentido de Sense con el soporte (OCBS-LA09)

## Especificación:

Características de presentación	
Fuente de luz:	650nm visible
Rango de escaneo:	200 escaneos por segundo
UPC	32 bit
Distancia de lectura	2.5 ~ 600 mm (100% UPC / EAN)
Ancho de escaneo	50 mm a 60 mm, 220 mm a 200 mm
Tipo de escáner:	Bi-direccional
Modo de operación	Sentido automático
Resolución:	Serie de 3mil series de alta resolución / serie de campo de profundidad larga 5mil
Mínimo de contraste de impresión:	30%, diferencia mínima de reflexión
Capacidad de decodificación:	UPC / EAN, UPC / EAN con suplementarios, UCC / EAN 128, Código 39, Código 39 ASCII completo, Código trióptico 39, Código 128, Código 128 ASCII completo, Codabar, Intercalado 2 de 5, Discreto 2 de 5, Código 93, MSI, código 11, variantes RSS, chino 2 de 5, MSI / Plessey, UK / Plessey, UCC / EAN 128, código chino, serie GS1 DataBar (RSS)
Angulo de escaneo	± 65 ° (inclinación); ± 60 ° (tono); ± 42 ° (guiñada)
Características físicas	
Interfaces compatibles:	PS2, RS232, USB para la opción
Voltaje:	5V DC ± 5%
Corriente:	85 mA (en funcionamiento); 100 (máximo)
Indicador	Beeper, LED
Material	ABS + PC
Estar	Con
Dimensiones:	156 * 68 * 83 mm (L * W * H)
Peso:	235g
Color:	Gris o negro
Entorno de usuario	
Temperatura de funcionamiento:	0 °C ~ 45 °C
Temperatura de almacenamiento:	-40 °C ~ 60 °C
Humedad:	5% -90% (sin condensación)
Descarga electrostática:	Cumple con +/- 15KV de descarga de aire y +/- 8KV de descarga de contacto
Iluminación ambiental	0 ~ 100,000 LUX
Especificaciones de caída:	Soporta múltiples caídas de 1.5m en una superficie de concreto
Clasificación láser	EN60825-1, clase 1

## Detalles del producto:





## Features

**Simple but not easy**

200scan/sec high scan rate and long reading distance;





Excellent decode capability;



KBW, RS232 and USB supported;



Durable construction combined with future-proofing





Competitive price for 32bit model



## || All-round show





## Parameter

Performance Characteristics	
Light Source:	650nm visible
Scan Rate:	200 scans per second
CPU	32 bit
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Width of Scan	50mm@60mm, 220mm@200mm
Scanner Type:	Bi-directional
Operation mode	Auto Sense
Resolution:	3mil high resolution series / 5mil long depth field series
Print Contrast Minimum:	30%, minimum reflective difference
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar

	Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, chinese code , GS1 DataBar (RSS) series
Scanning Angle	±65°(tilt); ±60°(pitch); ±42°(yaw)
<b>Physical Characteristics</b>	
Interfaces Supported:	PS2, RS232, USB
Voltage:	5V DC±5%
Current:	85 mA (Operating); 100 (Max)
Indicator	Beeper, LED
Material	ABS+PC
Stand	Optional
Dimensions:	156*68*83 mm (L*W*H)
Weight:	235g
Color:	Grey and black
<b>User Environment</b>	
Operating Temperature:	0°C~45°C
Storage Temperature:	-40°C~60°C
Humidity:	5%-90% (non-condensing)
Electrostatic Discharge:	Conforms to +/-15KV air discharge and +/-8KV of contact discharge
Ambient Illumination	0 ~ 100,000 LUX
Drop Specifications:	Withstands multiple 1.5m drops to concrete surface
Laser classification	EN60825-1, class 1

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which

3. INTERNATIONAL AIR MAIL, usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com),  
Together we quest for the best.

