

# Módulo de escáner de código de barras fijo 2D

(N.º de Modelo.: OCBS -F3100 / F4100)

## CARACTERÍSTICA:

Motor: 31.7 mm (L) x 12.2 mm (H) x 12 mm (D);

Tarjeta de decodificación: 38 mm (L) x 19 mm (W) x 7,5 mm (D);

Fuente de luz: Aimer: LED de 617 nm, Iluminación: LED de 625 nm;

Campo de visión: 39 ° (H) x 25 ° (V);

Rodillo: 0 - 360 °;

Parcela: ± 65 ° o mayor;

Guiñada: ± 60 ° o mayor;

Contraste de impresión: 25% de diferencia reflectiva mínima;

OCBS -F4100: con estuche y cable de datos;

OCBS -F3100: sin estuche & cable de datos.



## Symbology Decode Capability

1D: UPC/EAN, UPC/EAN with supplementals, ISSN, BooklandEAN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39 Full, ASCII, Code93, Code11, Matrix 2 of 5, Code 32, Interleaved 2 of 5, Code 39, Trioptic Code 39, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 DataBar, ISBT Concat Korean 3 of 5, Variants

2D: PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec

Motion Tolerances: Up to 25 in. / 63.5 cm per second

Interfaces Supported: USB: HID Keyboard (default mode),  
COM Port Emulation

RS232: Standard

Minimum Resolution:      -SR: Code 39 4.8mil, UPC 60% 5 mil,  
  PDF417 5 mil,Datamatrix 7.5 mil  
  -HD: Code 39 3 mil, UPC 60% 5 mil,  
  PDF417 4 mil,Datamatrix 4.8 mil

Power Supplies:      Power supplies are available for applications that do not supply power over the host cable.

## **REGULATORY**

Electrical Safety:      UL60950-1 2nd ed, CSA C22.2 No. 60950-1 2nd ed,  
  EN60950-1/IEC60950-1 2nd ed.  
LED Safety:             IEC/EN60825-1:2001, IEC/EN62471:2006  
EMI/RFI:                FCC Part 15 Class B, ICES-003 Class B,  
  EN55022 Class B, EN55024  
Environmental:         Compliant with RoHS directive 2002/95/EEC

## **WARRANTY**

Subject to the terms of OCOM 's hardware warranty statement, the 3100 is warranted against defects in workmanship and materials for a period of 1 years from the date of shipment. For the complete OCOM hardware product. warranty statement, go to: <http://www.ocominc.com>

## **User Environment**

Operating Temp:         0° C to 55° C  
Storage Temp:           -40° C to 60° C  
Humidity:                5% to 95%, non-condensing  
Drop Spec:              Withstands multiple 6 ft. drops to concrete  
Ambient Light:         Immune to normal indoor lighting up to 1600 Lux.  
Immunity:               Immune to sunlight up to 86,000 Lux.

## **Accessories**

Interface board and cable

Rendimiento típico *	Rangos de trabajo típicos	
	Rango de enfoque HD	Rango de enfoque SR

Tipo de código de barras	Densidad de símbolos	Cerca	Lejos	Cerca	Lejos
Código 39	5.0 mil	0mm	90mm	60mm	130mm
100% UPCA	13.0 mil	5mm	180mm	30mm	300mm
Código 39	20.0 mil	5mm	250mm	35mm	350mm
PDF 417	6.8 mil	0mm	85mm	40mm	150mm
Matriz de datos	10.0 mil	0mm	70mm	50mm	130mm
Código QR	20.0 mil	0mm	180mm	25mm	250mm
Resolución 1D Código 39		3 mil (0.076mm)		5 mil (0.127 mm)	
Resolución 2D Matriz de datos		5 mil (0.127 mm)		6.7 mil (0.170mm)	
* El rendimiento puede verse afectado por la calidad del código de barras y las condiciones ambientales.					

