

Escáner de código de barras láser con soporte

(Modelo: OCBS-LA06)

Característica:

- 1.Auto-inducción incorporada, diseño verde;
2. Alta escanear tasa y distancia de lectura de largo;
- 3.Excellent decodificar la capacidad;
- 4.KBW, RS232 y USB compatibles;
- Construcción 5.Durable combinado con futuro a prueba;

Especificación:

Características de rendimiento	
Fuente de luz:	Láser visible (650-670nm)
Velocidad de lectura:	100 lecturas por segundo
Distancia de lectura	2.5 ~ 600 mm (100% UPC / EAN)
Tipo de escáner:	Bidireccional
Resolución:	0.10mm (4mil) a PCS 0.9
Contraste de impresión mínimo:	20%, diferencia mínima reflectante (@ 650nm)
Capacidad de decodificación:	UPC / EAN, UPC / EAN con supplementals, UCC / EAN128, el código 39, código 39 ASCII completo, código 39 TriOptic, código 128, código 128 ASCII completo, codabar, entrelazado 2 de 5, discreto 2 de 5, Código 93, MSI, código 11, ATA, las variantes de RSS, China 2 de 5 ...
Características físicas	
Interfaces compatibles:	PS2, RS232, USB
Voltaje:	DC + 5V +/- 5%
Corriente:	100 mA
Idle actual:	& lt; 40 mA
Fuente de alimentación:	Anfitrión poder o (RS232) fuente de alimentación externa
Ángulo de barrido	Inclinación 45 ° de elevación de 60 °
Dimensiones:	L165.42mm X W69.72mm X H89.67mm
Peso:	140g (sin base)
Estar	Con
Color:	Marfil y negro
Entorno de usuario	
Temperatura de funcionamiento:	0 °C ~ 50 °C
Temperatura de almacenamiento:	-40 °C ~ 70 °C
Humedad:	5 ~ 95% de humedad relativa, sin condensación
Descarga electrostática:	Confirmar a +/- descarga de aire 15KV y +/- 8KV de descarga de contacto
Caída de Especificaciones:	Soporta múltiples caídas sobre hormigón de 1,5 m

A salvo:	
EMI / RFI:	FCC Clase A y CE
Seguridad del láser:	Clase CDRH producto 2 láser





Features

Simple but not easy

Auto-Induction built in, green design



High scan rate and long reading



High scan rate and long reading distance



Excellent decode capability



KBW, RS232 and USB supported

Durable construction combined with future-proofing



All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
Physical Characteristics	

Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	With
Color:	Ivory and black
User Environment	
Operating Temperature:	0°C~50°C
Storage Temperature:	-40°C~70°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product


Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.



