POS LED Cliente Polo de Despliegue
(Modelo: LED8A)

Presupuesto:

Comunicación	
Interfaz:	la comunicación RS232, fuente de alimentación del USB (CC opcional)
Velocidad de transmisión:	2400 / 9600BPS
Brillo:	1500cd
la señal del apretón de manos	No
Eléctrico	DC 5V (de interfaz de host USB del ordenador)
Monitor:	pantalla digital de color amarillo verdoso brillante LED
Los caracteres de presentación:	8 Números (0 ~ 9)
Área de visualización:	160mm x 30.8mm
Tamaño de fuente:	13MM * 7.6mm
MTBF:	25.000 horas
Físico	
Dimensiones del panel:	224 (L) X88 (W) mm
dimensiones del apoyo:	Altura: 400 --- 442mm Base: 185 (L) x95 (W) x 25 (H) mm
Lanzando ángulo de movimiento:	8 ° ~ 120 °
Color	Blanco o negro
Peso:	520g (sin la base); 850g (con base); 1100g (incluyendo el embalaje)
Tamaño de embalaje	255 (L) x 210 (W) x 96 (H) mm
Ambiente	
Temperatura de funcionamiento:	-40 ℃ -50 ℃
Temperatura de almacenamiento;	--El 80 ℃ -60 ℃
Humedad:	30% - 85%

Detalles del producto:

LED Customer Display

LED8A

Product Picture

Features

Simple but not easy

8 characters LED display;

Pole height is adjustable;

360 degree rotation angel;

Compatible with "ESC / POS"

standard common instruction set,

no need driver, plug and use;

All-round show

Application Area

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop
Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop
Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Parameter

Communication	
Interface:	RS232 communication, USB power supply (DC optional)
Baud rate:	2400/9600BPS
Brightness:	1500cd
Handshake signal	No
Electrical	DC5V (from host computer USB interface)
Display:	LED Bright yellow-green digital display
Display characters:	8 Numbers (0~9)
Display area:	160mm ×30.8mm
Font size:	13MM*7.6MM
MTBF:	25,000 hours
Physical	
Panel dimensions:	224(L)X88(W)mm
Support dimensions:	Height: 400---442mm Base: 185(L) x95(w) x25(H) mm
Pitching move angle:	8°~120°
Color	White or Black
Weight:	520g (without base);850g (with base);1100g (including packing)
Packing Size	255(L) x 210(W) x 96(H) mm
Environment	

Operating Temp:	-40℃--50℃
Storage Temp;	-60℃--80℃
Humidity:	30%--85%

Production Line

Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

✓ *Indicates information has been verifed onsite by TUV on 2013.7.15*

Quality Assurance

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfication.

Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment.Some designated models can have as long as 24 months warranty.

Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6

✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

✓ *Indicates information has been verifed onsite by TUV on 2013.7.15*

Certifications

Packing and Shipment



CHINA POST

Payment

Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have estabilshed goods relationship with our customers and have friendly communication with each other.

Why you choose us?

Company Profile

This Assessed Supplier Has Been
Independently Verified

Build Your Growth On Trust

TÜVRheinland®
Precisely Right.

OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals . Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Eruope, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.

Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China;
Websites: http://www.possolution.com.cn ; http://www.ocominc.com ;
E-mail: ocom@ocominc.com , ocomtech@gmail.com ;
Skype: ocominc2000, ocominc;
MSN: ocomtech@hotmail.com, ocominc@hotmail.com;
Trademanager: szocominc, cn1500439666;
QQ: 2485890637,190852203;
Tel/Fax: +86.755.8605.3207.

Documentos importantes:

¿Quieres saber más inf productoormación?Por favor Haga clic aquí.

Especificación
Manual de usuario
Conductor