Bluetooth o 433MHZ Wireless 2D Barcode Scanner (OCBS-W230 / OCBS-W230B)

Parámetros:

Puntería	
	617 LED nm
Fuente De	
Luz	
Iluminaci	625 LED nm
ón Fuente	
De Luz	
	39 ° (H) x 25 ° (V)
n Ángulo	
	0 - 360 °
Ángulo	
Elevación :	+ 65 °
Ángulo	± 03
Inclinació :	+ 60 °
n Ángulo	± 00
	Comparison del 250/
	Superior del 25%
Contrasta	
r	
1	UPC / EAN, UPC / EAN con supplementals, BooklandEAN, ISSN, Cupón UCC
	Extended Código, Code128, GS1-128, ISBT 128, Código 39, Código 39 ASCII
	completo, TRIOPTIC Código 39, Código 32, Código 93, Code11, Matrix 2 de 5,
	Interleaved 2 de 5, discreta 2de 5, Codabar, MSI, chino 2 de 5, GS1 Data
	Barvariants, coreano 3 de 5, ISBT Concat
2D	PDF417, MicroPDF417, Códigos compuestas, TLC-39, Datos Matrix, Maxicode,
1 4	Código QR, MicroQR, azteca
l ľ	
	USB
Interfaz	USB
Interfaz Comunica	
Interfaz Comunica ción	USB
Interfaz Comunica ción distancia	USB Interior: 100m; Exterior: 300m (Max)
Interfaz Comunica ción distancia Operativo	USB Interior: 100m; Exterior: 300m (Max)
Interfaz Comunica ción distancia Operativo Temperat	USB Interior: 100m; Exterior: 300m (Max)
Interfaz Comunica ción distancia Operativo Temperat ura	USB Interior: 100m; Exterior: 300m (Max) -10 ° C - 45 ° C
Interfaz Comunica ción distancia Operativo Temperat ura Almacena	USB Interior: 100m; Exterior: 300m (Max)
Interfaz Comunica ción distancia Operativo Temperat ura Almacena miento	USB Interior: 100m; Exterior: 300m (Max) -10 ° C - 45 ° C
Interfaz Comunica ción distancia Operativo Temperat ura Almacena miento Temperat	USB Interior: 100m; Exterior: 300m (Max) -10 ° C - 45 ° C
Interfaz Comunica ción distancia Operativo Temperat ura Almacena miento Temperat ura	USB Interior: 100m; Exterior: 300m (Max) -10 ° C - 45 ° C -20 ° C - 65 ° C
Interfaz Comunica ción distancia Operativo Temperat ura Almacena miento Temperat ura Operativo	USB Interior: 100m; Exterior: 300m (Max) -10 ° C - 45 ° C -20 ° C - 65 ° C
Interfaz Comunica ción distancia Operativo Temperat ura Almacena miento Temperat ura Operativo Humedad	USB Interior: 100m; Exterior: 300m (Max) -10 ° C - 45 ° C -20 ° C - 65 ° C 5% -85%
Interfaz Comunica ción distancia Operativo Temperat ura Almacena miento Temperat ura Operativo Humedad Almacena	USB Interior: 100m; Exterior: 300m (Max) -10 ° C - 45 ° C -20 ° C - 65 ° C 5% -85%
Interfaz Comunica ción distancia Operativo Temperat ura Almacena miento Temperat ura Operativo Humedad Almacena miento	USB Interior: 100m; Exterior: 300m (Max) -10 ° C - 45 ° C -20 ° C - 65 ° C 5% -85%
Interfaz Comunica ción distancia Operativo Temperat ura Almacena miento Temperat ura Operativo Humedad Almacena miento	USB Interior: 100m; Exterior: 300m (Max) -10 ° C - 45 ° C -20 ° C - 65 ° C 5% -85% 5% -95%
Interfaz Comunica ción distancia Operativo Temperat ura Almacena miento Temperat ura Operativo Humedad Almacena miento Humedad Durabilid	USB Interior: 100m; Exterior: 300m (Max) -10 ° C - 45 ° C -20 ° C - 65 ° C 5% -85%
Interfaz Comunica ción distancia Operativo Temperat ura Almacena miento Temperat ura Operativo Humedad Almacena miento Humedad Durabilid ad	USB Interior: 100m; Exterior: 300m (Max) -10 ° C - 45 ° C -20 ° C - 65 ° C 5% -85% Soporta múltiples caídas sobre hormigón de 1,8 m
Interfaz Comunica ción distancia Operativo Temperat ura Almacena miento Temperat ura Operativo Humedad Almacena miento Humedad Durabilid ad	USB Interior: 100m; Exterior: 300m (Max) -10 ° C - 45 ° C -20 ° C - 65 ° C 5% -85% 5% -95%

Luminatio Interior: 3.000 L	IV may, La luz color o	storior 960001 IV max			
	DA IIIAX; La luz solar e	xterior: ooooolox max			
n Elifo					
EMC EN50081, norma					
FCC EN50082, norma	par1				
IP Grado IP42					
DECODE RANGOS					
D 1!! 1/! ¥		Los rangos de trabajo	Los rangos de trabajo típicos		
Rendimiento típico *		HD Rango de enfoque			
Bar Código Tipo	Símbolo Densidad	Cerca	Lejos		
Código 39	5.0 mil	5mm	90mm		
100% UPCA	13.0 mil	8mm	200mm		
Código 39	20.0 mil	8mm	250mm		
PDF 417	6.8 mil	5mm	95mm		
Datos Matriz	10.0 mil	5mm	110mm		
QR Código	20.0 mil	10mm	150mm		
Resolución Código 1D 39	Resolución Código 1D 39 2.8 mil (0.071mm)				
Resolución Data Matrix 2D	Resolución Data Matrix 2D 4.8 mil (0.122mm)				
Material	ABS + PC				
Dimensión	95x65x155mm				
Neto Peso	160g				
Interior Dimensión de la 18.2X11.7X11.2					
caja:					
Interior Peso de la caja: 374g					





Bookstore



Supermaket




Pharmacy





Warehouse





Restaurant

Parameter			
Physical Characteristics			
Dimension	95x65x155mm		
Material	ABS+PC		
Net Weight	160g		

Att	C17	Optical Performanc	e		
Aiming Light Source	617 nı		In.		
Lighting Light Source	625 nm LED				
Scanning Angle) x 25° (V)		W UV	
Rotation Angle	0 - 360) _e		100	
Elevation Angle	75.05.55	± 65°			
Tilt Angle	± 60°	# 19/24-00/00 day 99/00			
Print Contrast	Higher than 25%				
1D	Coupo FullAS Interle	on Extended Code, Code128, CII, Trioptic Code 39, Code	ementals, BooklandEAN, IS GS1-128, ISBT 128, Code 39 32, Code 93, Code11, Matr 5, Codabar, MSI, Chinese 2	, Code 39 ix 2 of 5,	
2D	TATE OF STREET	7, MicroPDF417, Composite de, MicroQR, Aztec	Codes, TLC-39, Data Matrix, N	Maxicode,	
Interface	USB	4004.00 (1975) (1975) (1975) (1975)			
Communication distance	Inside	: 100m; Outside: 300m (M	ax)		
Operating Temperature	-10°0	C -45℃	inc. it		
Storage Temperature	-20°C	C -65°C	V	00	
Operating Humidity	5%-85	%		any.	
Storage Humidity	5%-95	%	lin .	A)	
Durability	Withs	tands multiple 1.8m drops to	concrete		
Input Power	DC 5V	, 350mA			
Lumination	Inside	: 3.000 LUX max; Outside	sunlight: 86000LUX max		
EMC	EN500	81, par1 standard			
FCC	EN500	82, par1 standard			
IP Grade	IP42				
		DECODE RANGES	60	Silve	
Typical Performance*			Typical Working Ranges		
			HD Focus Range		
Bar Code Type		Symbol Density	Near	Far	
Code 39		5.0 mil	5mm	90mm	
100% UPCA	VOII.	13.0 mil	8mm	200mm	
Code 39		20.0 mil	8mm	250mm	
PDF 417		6.8 mil	5mm	95mm	
Data Matrix		10.0 mil	5mm	110mm	
QR Code		20.0 mil	10mm	150mm	
Resolution 1D Code 39		1/1/17	2.8 mil (0.071mm)	W	
				1.00	



OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers'satisfaction.

Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHs and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments:

✓ Indicates information has been verified onsite by a certification specialist.

Test Equipment and Facilities

Verified	Machine Name	Brand & Model No.	Quantity
1	Ageing Tester	No Information	6
1	Withstand Voltage Tester	CC2670A	1
1	Oscilloscope	TBS1102	1
1	DC Power Supply	PS-305DM	6
1	Digital Torque Meter	HP100	1
1	Calliper	GUANGLU	2
1	Multi-meter	VC890D	7
V	Test Computer	No Information	13

Verified by TUV on 2013.7.15

Certification:









Warranty and After Sales:

- All products' warranty are not less than 12 month, some models even up to 24 months warranty.
- Spare parts will be provided for mass orders for customers' local maintenance.
- Any product found to be defective within 30 days of shipment shall be deemed Dead on Arrival (DOA). DOA products will be advance replaced and shipped via express.
- Have distributors or authorized agents in the main market who can provide local repair and replacement services.
- Professional CRM management insures fast respond for customer's enquiries and orders tracking.
- Sales with many years experience in foreign trade, proficient in foreign languages and strong sense of responsibility.
- 7*24 hours online, responds with 12 hours in working days, and within 24 hours for rest days.































secure payment







Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have estabilshed goods relationship with our customers and have friendly communication with each other.





Company Profile



TRADE ASSURANCE

- 0100% money refund for Late shipment&Quality problem
- Guarantee on-time delivery
- Third-party pre-shipment quality inspection (Optional)
- No transaction commission charged
- The HIGHEST assurance amount guaranteed by alibaba
- in the Auto-ID and POS industry .



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers, Thermal Printer, Barcode printer, Dot Matrix Printer, Barcode Scanner, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs. OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.















Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: Unit701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan

District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn; E-mail: ocom@ocominc.com, info@possolution.com.cn;

Tel: +86.755.86053207 ext 800; Fax: +86.755.86053207 ext 868; QQ: 2485890637, 190852203; Wechat: szocominc, hj34924238; Whatsapp: 008613352932860;



Documentos importantes:

- *Especificación
- * Manual De Usuario