

Escáner de código de barras 2D inalámbrico de alta calidad con cuna

Modelo: OCBS-w231

Características:

- 1, distancia de comunicación inalámbrica 433 MHz al aire libre 300 m, 100 m de interior; Distancia de comunicación inalámbrica Bluetooth exterior 20 m, y 10 m de interior;
- 2, equipado de la comunicación y de la base de carga
- 3, cubierta plástica suave para proteger la lente y el contorno realza grandemente el funcionamiento anti-Drop;
- 4, código de barras en la pantalla de los ordenadores y de los teléfonos móviles puede ser explorado;
- 5, ningún conductor de la necesidad, enchufe y juego;
- 6, puede almacenar más de 10.000 pedazos de datos;
- 7, los escáneres múltiples se pueden conectar a un receptor (433 MHz).

Parámetros:

Apuntando la fuente de luz	617 nanómetro LED
Fuente de luz de iluminación	625 nanómetro LED
Ángulo de exploración	39 ° (h) x 25 ° (v)
Ángulo de rotación	0-360 °
Ángulo de elevación	± 65 °
Ángulo de inclinación	± 60 °
Contraste de impresión	Superior al 25%
1D	UPC/EAN, UPC/EAN con los suplementos, BooklandEAN, ISSN, código extendido del cupón de UCC, Code128, GS1-128, ISBT 128, código 39, código 39 Full ASCII, código trióptico 39, código 32, código 93, Code11, matriz 2 de 5, 2 de 5, 2 discreto 5, Codabar, MSI, Chino 2 de 5, datos GS1 Barvariants, Coreano 3 de 5, ISBT concat
2D	PDF417, MicroPDF417, códigos compuestos, TLC-39, matriz de datos, Maxicode, código QR, MicroQR, Azteca
Interfaz	USB (cable receptor wireless)
Distancia de la comunicación	433 MHz: dentro de: 100 m; Fuera de: los 300 m (máximos) Bluetooth: dentro de: 10 m; Fuera de: 20 m (máximo)
Temperatura de funcionamiento	-10 deg c-45 deg c
Temperatura de almacenaje	-20 DEG c-65 deg c
Humedad de funcionamiento	5%-85%
Humedad del almacenaje	5%-95%
Durabilidad	Soporta múltiples gotas de 1,5 m al concreto
Energía de entrada	C.c. 5V, 280mA
Tiempo de carga	6
Batería	1500mAh
Lumination	Dentro de: 3,000 lux máximo; Luz del sol exterior: 86000LUX máximo

Grado del IP	IP42		
Decodificación de rangos			
Rendimiento típico *	Gammas de trabajo típicas		
	Gama de enfoque HD		
Tipo de código de barras	Densidad del símbolo	Cerca	Lejos
Código 39	5,0 mil	5	90
100% UPCA	13,0 mil	8	200
Código 39	20,0 mil	8	250
PDF 417	6,8 mil	5	95
Matriz de datos	10,0 mil	5	110
Código QR	20,0 mil	10	150
Resolución 1D código 39	4 mil		
Matriz de datos 2D de resolución	10 mil		
Material	ABS + PC		
Dimensión	Base del explorador (70 * 95 * 168) (145 * 112 * m)		
Peso neto	Escáner 185 base 186g		
Información de pedidos:	OCBS-W231-4: 433 MHz inalámbricas de código de barras 2D escáner con cuna		
	OCBS-W231-b: Bluetooth 2D barocde escáner con cuna		



FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE



LONG DISTANCE WIRELESS COMMUNICATION



STRONG DECODING ABILITY



CHARGING CRADLE



STABLE STRUCTURE



NO NEED DRIVER, PLUG AND PLAY

1

FAST SCAN,HIGH RECOGNITION RATE



2

STRONG DECODING ABILITY



3

CRADLE FOR CHARGING AND WIRELESS COMMUNICATION



4

STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE



5

NO NEED DRIVER PLUG AND PLAY



THE PRODUCT FAMILY



PRODUCT PACKAGING FIGURE



WIDE RANGE OF APPLICATION,RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE,THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



**PRODUCT
INORMATION**

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Bar variants, Korean 3 of 5, ISBT Concat
2D	PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec
Interface	USB (Wireless receiver cable)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h
Battery	1500mAh
Lumination	Inside: 3.000 LUX max; Outside sunlight: 86000LUX max
IP Grade	IP42

DECODE RANGES			
Typical Performance*		Typical Working Ranges	
		HD Focus Range	
Bar Code Type	Symbol Density	Near	Far
Code 39	5.0 mil	5mm	90mm
100% UPCA	13.0 mil	8mm	200mm
Code 39	20.0 mil	8mm	250mm
PDF 417	6.8 mil	5mm	95mm
Data Matrix	10.0 mil	5mm	110mm
QR Code	20.0 mil	10mm	150mm
Resolution 1D Code 39	4 mil		
Resolution 2D Data Matrix	10 mil		
Material	ABS+PC		
Dimension	Scanner (70*95*168mm) Base (145*112*74mm)		
Net Weight	Scanner 185g Base 186g		
Ordering Info.	433MHz wireless communication (OCBS-W231-4)		
	Bluetooth communication (OCBS-W231-B)		

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.



Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: sales15@ocominc.com

Tel: 0086.755.86053207-815;

Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: [ocomsales15](https://www.wechat.com/qrcode/index?qr=ocominc);

Whatsapp: +0086.189.4879.9080;

Documentos relevantes:

[Manual del usuario](#)

Vídeo de los productos:

Específico del producto:[OCBS-W231 433 MHz o Bluetooth sin hilos QR Code 2.o código de barras escáner con cuna](#)