

OCBS-W800 433MHz código de barras de mano inalámbrico escáner de 32 bits

PRESUPUESTO:

| characterstics FÍSICAS | |
|--|--|
| Fuente de luz: | Diodo láser visible (VLD) @ 650 nm |
| Dimensiones del escáner : | 168mm * 72mm * 93mm (W * D * H) |
| Dimensiones del receptor: | 130mm * 45mm * 129mm (W * D * H) |
| Material: | ABS + TPR / aleación de aluminio |
| Peso: | 370g |
| Modo de exploración: | Portátil; Modo de escaneo continuo. |
| Luz indicadora: | LED rojo y azul |
| Zumbador: | Volumen del timbre ajustable |
| characterstics RENDIMIENTO | |
| Anchura del campo de la exploración: | @ 60mm 30mm (De cara del motor) @ 98 mm 100 mm (desde el frontal del motor) |
| Profundidad de campo de la exploración: | 10-450mm (Contraste 0,9 Densidad 0,25) |
| Velocidad de escaneo: | 150 lecturas / seg |
| La precisión de la exploración: | 0.10-0.825mm |
| Tasa de error de bit: | 1.5 millones) |
| Capacidad de decodificación: | UPC / EAN, UPC / EAN con con suplementos, UCC / EAN128, Código 39, Código 39 ASCII completo, TRIOPTIC Código 39, Código 128, Código 128 ASCII completo, Codabar, Interleaved 2 de 5, discreto 2 de 5, Código 93, MSI, El código 11, las variantes de RSS, chino 2 de 5, MSI / Plessey, Reino Unido / Plessey, EAN 128, código chino, GS1 serie UCC / (RSS) |
| Batería: | 3.7V / 750mAh, Li-ion |
| Tiempo de carga: | 3.0 Horas |
| Tiempo de análisis: | 30 Horas |
| Corriente: | 95mA (de trabajo); 25 mA (en espera) |
| Anglos: | Paso: 60 °; Inclinación: 45 ° |
| Frecuencia de trabajo: | 433MHz |
| Distancia de comunicación: | 200m (lugares abiertos) |
| Interface de comunicación: | USB |
| Characterstics entorno de usuario | |
| Temperatura: | -10degree Cto 45grados C (En funcionamiento), -40degree Cto 60 grados C (almacenamiento) |
| Humedad relativa: | 5% -90% (sin condensación) |
| Especificación de caídas: | Soporta caídas continuas de 1,5 m de superficie de hormigón |
| La iluminación ambiente: | 0 ~ 100.000 LUX |
| Descarga electrostática: | Cumple con la descarga de aire ± 12KV y ± 6KV de descarga de contacto |
| Certificado de seguridad: | CE, FCC, Clase 2, RoHS |

Detalles del producto:



Wireless Barcode Scanner

OCBS-W800



Product Picture





Features

Simple but not easy

Integrated non-volatile memory



Data transmission distance reaches 200m in open area



Integrated non-volatile memory



Intelligent battery management system, real-time check the remaining battery



32bit decoder ensuring excellent decoding ability



All-round show





Parameter

| PHYSICAL CHARACTERISTICS | |
|--------------------------------|---|
| Light Source | Visible Laser Diode (VLD) @ 650 nm |
| Memory | 128K |
| Scanner Dimensions(W * H * D) | 168mm * 72mm * 93mm |
| Receiver Dimensions(W * H * D) | 130mm*45mm*129mm |
| Material | ABS+TPR /Aluminium alloy |
| Weight | 370g |
| Scanning Mode | Hand-held; Continuous Scanning Mode. |
| Indicator Light | LED Red and Blue |
| Buzzer | Buzzer Volume Adjustable |
| PERFORMANCE CHARACTERISTICS | |
| Width of Scan Field | 60mm@30mm (From engine face) 98mm@100mm (from engine face) |
| Depth of Scan Field | 10-450mm (Contrast 0.9 Density 0.25) |
| Scan Speed | 150 scans/sec |

| | |
|---|---|
| Scan Precision | 0.10-0.825mm |
| Bit Error Rate | 1/(5million) |
| Decode Capability | UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese Code, GS1 DataBar (RSS) series |
| Battery | 3.7V/750mAh, Li-ion |
| Charge Time | 3.0 Hours |
| Scan Time | 30 Hours |
| Current | 95mA (working); 25mA(standby) |
| Angles | Pitch:60°; Tilt: 45° |
| Working Frequency | 433MHz |
| Communication Distance | 200m (Open Places) |
| Communication Interface | USB |
| USER ENVIRONMENT CHARACTERISTICS | |
| Temperature | -10°C to 45°C (Operating), -40°C to 60°C (Storage) |
| Relative Humidity | 5%-90%(Non-Condensing) |
| Drop Specification | Withstands repeated 1.5m drops to concrete surface |
| Ambient Illumination | 0~100,000 LUX |
| Electrostatic Discharge | Conforms to ±12KV air discharge and ±6KV of contact discharge |
| Safety Certificate | CE, FCC, Class 2, RoHS |

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at www.ocominc.com, Together we quest for the best.



Documentos importantes:

¿Quieres saber más inf productoormación?Por favor Haga clic aquí.

[Especificación](#)
[Manual de usuario](#)