

# China 80mm thermal receipt printer factory

(M/N:OCP-80G)

Printing method:	Direct thermal
Printing speed :	230mm/s □ 260mm/s
Roll width :	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line512 Dots/line
Line's pacing :	3.75mm □ Adjustable by commands □
Print command:	Compatible with the ESC/POS command
Interface type:	Serial+USB+Lan/36P parallel port/25P serial +USB/LAN
C utters life:	1million cuts
P rint head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor :	AC110V/240V □ 50~60Hz
Power supply :	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment :	Temperature(0 □ 45) humidity(10 □ 80%) □ No n- condense □
Work environment :	Temperature(0-45) degree centigrade, humidity(10-80%) No n- condense
Storage environment :	Temperature(-10 □ 60 °C ) ; H umidity(10 □ 90%)
Character size :	ANK □ FontA:1.5*3.0mm/ FontB □ 1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA □ EAN13 □ /JAN8 □ EAN8/CODE39/ITF /CODE93/CODE128 / QRCode /PDF417 (options)
Characters:	PC347 □ Standard Europe □□ Katakana □ PC850 □ Multilingual □□ PC860 □ Portuguese □□ PC863 □ Canadian-French □□ PC865 □ Nordic □□ West Europe □ Greek □ Hebrew □ East Europe □ Iran □ WPC1252 □ PC866 □ Cyrillic#2 □□ PC852 □ Latin2 □□ PC858 □ IranII □ Latvian □ Arabic □ PT151 □ 1251 □
Physical characteristics □	Weight : 1.25Kg ; Appearance size : 190×145×143 m m (length * width * height)

## Relevant documents:

[\\*Specification](#)

[\\*IP Address Configure Manual](#)

[\\*Instruction Manual](#)

[\\*Driver for all windows system](#)

[\\*Driver for Linux](#)

[\\*Printer Parameters Setting Tools](#)

[\\*CD Files](#)

