

433Mhz escáner de código de barras láser inalámbrico de 32 bits con cuna (Modelo: OCBS -W800)

PRESUPUESTO:

Características físicas	
Fuente de luz:	Diodo láser visible (VLD) a 650 nm
Dimensiones del escáner :	168 mm * 72 mm * 93 mm (W * H * D)
Dimensiones del receptor:	130 mm * 45 mm * 129 mm (W * H * D)
Material:	ABS + TPR / Aleación de aluminio
Peso:	370 g
Modo de escaneo:	Mano; Modo de escaneo continuo.
Luz indicadora:	LED rojo y azul
Zumbador:	Volumen del zumbador ajustable
CARACTERSTICAS DE RENDIMIENTO	
Ancho del campo de escaneo:	60mm @ 30mm [De la cara del motor] 98mm @ 100mm [de la cara del motor]
Profundidad del campo de escaneo:	10-450mm [Contraste 0.9 Densidad 0.25]
Velocidad de escaneo:	150 exploraciones por segundo
Precisión de escaneo:	0.10-0.825mm
Tasa de error de bit:	1 / (5million)
Capacidad de decodificación:	UPC / EAN, UPC / EAN con suplementarios, UCC / EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 de 5, Discrete 2 de 5, Code 93, MSI, Código 11, variantes RSS, chino 2 de 5, MSI / Plessey, Reino Unido / Plessey, UCC / EAN 128, Código chino, serie GS1 DataBar (RSS)
Batería:	3.7V / 750mAh, Li-ion
Tiempo de carga:	3.0 horas
Tiempo de escaneo:	30 horas
Corriente:	95mA (trabajando); 25mA (en espera)
Anglos:	Parcela: 60 °; Inclinación: 45 °
Frecuencia de trabajo:	433MHz
Distancia de comunicación:	200m [Lugares Abiertos]
Interface de comunicación:	USB
CARACTERSTICAS DEL ENTORNO DEL USUARIO	
Temperatura:	-10 grados Cto 45grado C (En funcionamiento), -40degree Cto 60degree C (Almacenamiento)
Humedad relativa:	5% -90% (sin condensación)
Especificación de la gota:	Soporta repetidas gotas de 1.5m a la superficie de concreto
Iluminación ambiental:	0 ~ 100,000 LUX
Descarga electrostática:	Cumple con una descarga de aire de $\pm 12KV$ y una descarga de contacto de $\pm 6KV$
Certificado de seguridad:	CE, FCC, Clase 2, RoHS

Detalles del producto:





Features

Simple but not easy



Integrated non-volatile memory

Data transmission distance reaches 200m in open area



Integrated non-volatile memory



Intelligent battery management system, real-time check the remaining battery



32bit decoder ensuring excellent decoding ability



All-round show





Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm
Memory	128K
Scanner Dimensions(W * H * D)	168mm * 72mm * 93mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	370g
Scanning Mode	Hand-held; Continuous Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm (From engine face) 98mm@100mm (from engine face)
Depth of Scan Field	10-450mm (Contrast 0.9 Density 0.25)
Scan Speed	150 scans/sec

Scan Precision	0.10-0.825mm
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese Code, GS1 DataBar (RSS) series
Battery	3.7V/750mAh, Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	95mA (working); 25mA(standby)
Angles	Pitch:60°; Tilt: 45°
Working Frequency	433MHz
Communication Distance	200m (Open Places)
Communication Interface	USB
USER ENVIRONMENT CHARACTERISTICS	
Temperature	-10°C to 45°C (Operating), -40°C to 60°C (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at www.ocominc.com, Together we quest for the best.



Documentos importantes:

¿Quieres saber más producto información? Por favor Haga clic aquí.

[Especificación](#)
[Manual de usuario](#)