Pos Laser Barcode Scanner

(Modelo: OCBS-LA04)

ESPECIFICACIONES:

ESPECIFICACIONES:	
Rendimiento Característica	S
Luz Fuente:	Visible láser (650-670nm)
Tomografía Calificación:	100 lecturas por segundo
Lectura Distancia	2.5 ~ 600 mm (100% UPC / EAN)
Escáner Tipo:	Bi-direccional
Resolución:	0.10mm (4mil) a PCS 0.9
Impresión Contraste mínima:	20%, diferencia mínima reflectante (@ 650nm)
Descodificar Capacidad:	UPC / EAN, UPC / EAN con supplementals, UCC / EAN128, el código 39, código 39 ASCII completo, código 39 TriOptic, código 128, código 128 completa ASCII, codabar, Interleaved 2 de 5, discreta 2 de 5, código 93, MSI, código 11, ATA, las variantes de RSS, chinos 2 de 5
Físico Características	
Interfaces Apoyado:	PS2, RS232, USB
Voltaje:	DC + 5V +/- 5%
Actual:	100 mA
Ocioso Actual:	& Lt; 40 mA
Energía Fuente:	Anfitrión poder o externa (RS232) Fuente de alimentación
Exploración Ángulo	Inclinación 45 ° de elevación de 60 °
Dimensiones:	L165.42mm X W69.72mm X H89.67mm
Peso:	140g (sin base)
Estar de pie	Con
Color:	Marfil y negro
Usuario Medio ambiente	
Operativo Temperatura:	0 °C ~ 50 °C
Almacenamiento	-40 °C ~ 70 °C
Temperatura:	C OFO(house deducted as a few assistance of a
Humedad:	5 ~ 95% humedad relativa, sin condensación
Electrostático Descarga:	Confirmar a +/- 15KV descarga de aire y +/- 8KV de descarga de contacto
Gota Especificaciones:	Soporta múltiple 1.5m gotas sobre hormigón
Seguro:	FOC Class Ass OF
EMI / RFI:	FCC Clase A y CE
Seguridad del láser:	CDRH clase 2 láser producto

Detalles del producto:



Product Picture











All-round show





Parameter

Performance Charact	eristics
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional Average State of the State of
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5
Physical Characterist	ics
Interfaces Supported:	DC2 DC232 LICE

interfaces oupported.	PO 504 500
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	With
Color:	Ivory and black
User Environment	
Operating Temperature:	0°C~50°C
Storage Temperature:	7-40°C~70°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	5~95% relative humidity, non-condensing Confirm to +/-15KV air discharge and +/-8KV of contact discharge Withstands multiple 1.5m drops to concrete
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

- 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
- 2. EXPRESS: around 3-7 working days to arrive
- INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which tination port

 By sea: depend on which destination port

 T/T destination port
- 4. By sea: depend on which destination port
- 5. T/T
- 6. Western Union

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.













Documentos importantes:

¿Quieres saber más inf productoormación?Por favor Haga clic aquí.

Especificación Manual del usuario