

1.dugramoramoramoramoramoramoramoramoroRameTroOo dlsiPAGAGAGAGación de calor Sistema
Hacer POS trabajar bien en un entorno más duro

2. La pantalla de pantalla táctil de super-supero y el diseño elegante mejoran su perfil más alto

3.mo RE ESTRUCTURA CIENTE SEPARADA PARA EL MANTENIMIENTO ENCENDIDO Y desmontaje

Modelo	- 1562-W	- 1562-A
Nombre	15. 6 pulgada tocar POS t erminal	
Alojamiento material	Carcasa de aleación de aluminio y base	
Pantalla principal	15. 6 Monitor de pantalla táctil de pulgadas , Panel IPS	
Resolución aficionado	1920*1080	
Brillo	22 0CD/m ²	
Vista a ngle	Horizonte: 90, Vertical : 60	
Tocar s grieta	Múltiple gg proyectado toque capacitivo	
Sub- mostrar	Pantalla de 11.6 pulgadas W/ o W/ O Función táctil para la opción	
Actuación		
Placa madre	Intel Celeron J 6412, 2.0GHz I ntel core i3 CPU para la opción	Rockchip Series RK3 568 , Quad Core 2.0 G
Sistema m emory	1*SO-D I m m DDR 4 ranura, soporte 3200MHz, 4GB /8GB /16G para la opción	A bordo DDR4 4GB, 8G para la opción
Dispositivo de almacenamiento	64 GB M.2 SSD o HIG h er, hasta 512 GB	a bordo de 32GB EMMC 64GB para la opción
Lan /Wlan	10/100 /1000 MBS, Realtek RTL8111f LAN Chip Mini ranura de Mini PCI-E incorporado, admite el módulo WiFi integrado	10/100 /1000 MBS, Realtek RTL8111f LAN Chip □ Apoyo Wi-Fi 802.11 a/ b/g/n , BT3.0/BT4.0
Operante s sistema	Windows 1 0 /11	Android 11
Conectividad		
Externo I /O puerto J 6412	P ower botón*1	
	12V DC en Jack*1	
	LAN: RJ-45*1 , USB*6, com*2, mini hdmi*1	
	Line Out & Mic en 2in1 Jack *1	
Externo Puerto de E/S RK3568	P ower botón*1	
	12V DC en Jack*1	
	LAN: RJ-45*1 , USB*6, com*1	
	Línea*1	
Ambiente		
Temperatura de funcionamiento	0 a 5 0 grados centígrados	
Temperatura de almacenamiento	- 2 0 a 60 grados centígrados	
Humedad de trabajo	10%~ 9 0% Sin condensación	
Humedad de almacenamiento	10%~ 90% Sin condensación	
Paquete		
Peso	Neto peso 3.6k g , g Ross peso 4.9k g	

Paquete con espuma en el interior	430*240 * 370 mm para una sola pantalla
Accesorios	
Adaptador de potencia	110-240V/50-60Hz AC Power i desglosar , DC12 V /5a adaptador de salida
Cable de alimentación	Enchufe de cable de alimentación compatible con EE. UU. / UE / Reino Unido, etc. y personalizado disponible



10mm Ultra-thin Body

High-end titanium gray color.
Modern stylish, industry new innovation.




Full Die-cast Aluminum Body

Uniform and delicate oxidized color,
more advanced than the painting process.



Full Lamination Advantage

Improved light transmittance ensure
high-definition display and higher
brightness to compatible with outdoor use.
Dust-free makes the screen cleaner.



Waterproof

Improved waterproof performance of the
surface, to avoid accidental water ingress.



High-Efficiency

Configured DDR4 3200MHz RAM and NVME
protocol M.2 SSD, faster response when operate.



Scientific Structural Design

Mainboard is sticked behind of lcd screen
ensuring maintenance convenient and
well-done cables management.



Specifications



OS
Windows 10/11
Android 11



Processor
Intel Celeron J6412
Rockchip RK3568



Memory
DDR4 4GB/8GB/16GB



Storage device
128G/256G/512G SSD
32G/64G/128G eMMC



Main screen
15.6" LCD (1920*1080)
16:9, Multi-point projected G+G capacitive touch



Sub-display
11.6"
Touch function for option



Interface
USB2.0*4, USB3.2*2, RJ48(Serial)*2,
1000Mbps LAN*1, Mini HDMI*1,
12V 5A DC input*1, Audio*1



Housing material
Aluminium alloy
Titanium grey



Options
3W Speaker
Wifi&Bluetooth
4G LTE



Environment
Operating temperature: 0°C - 50°C
Storage temperature: -20°C - 60°C



Size (W*H*D)
Product size: 370*180*296(mm)
Packaging size: 430*240*390(mm)



Weight
Net: 3.55kg
Gross: 4.9kg

Notice: Product specifications subject to change without prior notice. Product pictures are taken with engineering sample. OCOM reserves the right to change the product information without prior notice.

Website: www.ocominc.com









