

Escáner de código de barras láser inalámbrico de 24 GHz  
(Modelo: OCBS -W600)

**ESPECIFICACIÓN:**

CARACTERSTICAS FISICAS	
Fuente de luz:	Diodo láser visible (VLD) @ 650 nm-670nm
Dimensiones del escáner:	164 mm * 67 mm * 95 mm(Ancho * Alto * Profundo)
Dimensiones del receptor:	130 mm * 45 mm * 129 mm(Ancho * Alto * Profundo)
Material:	ABS + TPR / aleación de aluminio
Peso:	235g
Modo de escaneo:	Mano; Modo de escaneo bidireccional.
Luz indicadora:	LED rojo y azul
Zumbador:	Volumen del zumbador ajustable
CARACTERISTICAS DE RENDIMIENTO	
Ancho del campo de escaneo:	60 mm a 30 mm □ Desde la cara del motor □ 98 mm a 100 mm □ desde la cara del motor □
Profundidad del campo de escaneo:	2,5-600 mm □ Contraste 0.9 Densidad 0.25 □
Velocidad de escaneo:	100 escaneos / seg
Precisión de escaneo:	0,10 mm □ 4mil □ PCS0.9
Tasa de error de bit:	1 / (5 millones)
Capacidad de decodificación:	UPC / EAN, UPC / EAN con suplementos, UCC / EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Código 11, variantes de RSS, chino 2 de 5
Batería:	3,7 V / 750 mAh, iones de litio
Tiempo de carga:	3,0 horas
Tiempo de escaneo:	30 horas
Actual:	100mA (en funcionamiento); 40mA (en espera)
Anglos:	Paso: 60 °; Inclinación: 45 °
Distancia de comunicación:	30m
Frecuencia de trabajo:	2,4G
Memoria	16 MB
Interface de comunicación:	USB
CARACTERÍSTICAS DEL ENTORNO DEL USUARIO	
Temperatura:	0grado C hasta 50grado C (Operando), -40grado Chasta 70 grado C (Almacenamiento)
Humedad relativa:	5% -90% (sin condensación)
Especificación de caída:	Resiste caídas repetidas de 1,5 m sobre superficies de hormigón
Iluminación ambiental:	0 ~ 100.000 LUX
Descarga electrostática:	De acuerdo a ±Descarga de aire 12KV y ±6KV de descarga por contacto

Detalles de producto:





## Features

### Simple but not easy

2.4 G wireless laser barcode scanner



Scan Speed: 100scans/sec



Scan speed: 10000/second

Data transmission distance reaches 30m in open area;



Scan Time: 30hours



||| All-round show





## Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm-670nm
Scanner Dimensions(W * H * D)	164mm * 67mm * 95mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	235g
Scanning Mode	Hand-held; bidirectional Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm ( From engine face ) 98mm@100mm ( from engine face )
Depth of Scan Field	2.5-600mm ( Contrast 0.9 Density 0.25 )
Scan Speed	100 scans/sec
Scan Precision	0.10mm ( 4mil ) PCS0.9
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5
Battery	3.7V/750mAh, Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	100mA (working); 40mA(standby)

Angles	Pitch:60°; Tilt: 45°
Communication Distance	30m
Memory	2.4G
Communication Interface	USB ,RS232,PS2
<b>USER ENVIRONMENT CHARACTERISTICS</b>	
Temperature	0°C to 50°C (Operating), -40°C to 70°C (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.







We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com), Together we quest for the best.



Documentos importantes:

¿Quiere conocer más información sobre el producto? Haga clic aquí.

[Especificación](#)