Scanner de codes à barres laser portable
(Modèle: OCBS -L006)

Spécification:

Caractéristiques de performance	
Source de lumière:	Laser visible (650-670nm)
Taux de balayage:	100 numérisations par seconde
Distance de lecture	2,5 ~ 600 mm (100% UPC / EAN)
Type de scanner:	Bidirectionnel
Résolution:	0,10 mm (4 mil) à PCS 0,9
Contraste d'impression minimum:	20%, différence de réflexion minimale (@ 650 nm)
Capacité de décodage:	UPC / EAN, UPC / EAN avec supplément, UCC / EAN128, code 39, code 39 ASCII complet, code 39 trioptique, code 128, code 128 ASCII complet, barre de coda, entrelacé 2 sur 5, discret 2 sur 5, code 93, MSI, code 11, ATA, variantes RSS, chinois 2 sur 5...
Caractéristiques physiques	
Interfaces prises en charge:	PS2, RS232, USB
Tension:	DC + 5V +/- 5%
Courant:	100 mA
Courant de repos:	<40 mA
Source d'énergie:	Alimentation hôte ou alimentation externe (RS232)
Angle de balayage	Inclinaison 45 ° Élévation 60 °
Dimensions:	L165,42 mm X W69,72 mm X H89,67 mm
Poids:	140g (sans support)
Supporter	Sans pour autant
Couleur:	Ivoire et noir
Environnement utilisateur	
Température de fonctionnement:	0 degré C ~ 50 degrés C
Température de stockage:	-40 degrés C ~ 70 degrés C
Humidité:	5 ~ 95% d'humidité relative, sans condensation
Décharge électrostatique:	Confirmer à +/- 15KV de décharge d'air et +/- 8KV de décharge de contact
Spécifications de chute:	Résiste à plusieurs chutes de 1,5 m sur le béton
Sûr:	
EMI / RFI:	FCC Classe A et CE
Sécurité laser:	Produit laser CDRH classe 2

Détails du produit:

Handheld Laser Barcode Scanner

OCBS-L006

Product Picture

Features

Simple but not easy

High scan rate and long reading distance;

Excellent decode capability;

KBW, RS232 and USB supported;

All-round show

Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional

Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplemental, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, coda bar, interleaved 2 of 5,discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...
Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	Without
Color:	Ivory and black
User Environment	
Operating Temperature:	0 Degree C~50 Degree C
Storage Temperature:	-40 Degree C~ 70 Degree C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Production Line

Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

✓ *Indicates information has been verifed onsite by TUV on 2013.7.15*

Quality Assurance

OCOM is dedicated to providing most cost-effective products and

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfication.

Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services. OCOM's products have passed CE, FCC, TUV, RoHS and other certifications.

We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment.Some designated models can have as long as 24 months warranty.

Test Equipments

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

✓ *Indicates information has been verifed onsite by TUV on 2013.7.15*

Certifications

Packing and Shipment



DHL SUPPLY CHAIN · FedEx · UPS · TNT · EMS · 中国邮政 CHINA POST

Payment

WIRE TRANSFER · WESTERN UNION · MoneyGram · ESCROW · LC · AliExpress · PayPal

Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have estabilshed goods relationship with our customers and have friendly communication with each other.

Why you choose us?

Company Profile

OCOM Technologies Limited founded in 2007, it is one of leading suppliers of POS and Auto-ID related products from China.

OCOM's products portfolio covers Thermal Printer, Dot Matrix Printer, Barcode Printer, Barcode Scanner, Magnetic Card Reader, POS Terminal, and POS peripherals . Our products have passed CE, FCC, RoHS and other required certificates, and hot selling in Eruope, Australia, Asia, and other area.

OCOM has a professional teams including marketing, R&D, quality control, production and sales service. The management members have worked in the FORTUNE 500 companies as senior managers for many years, All of the sales have more than 5 years experience, which help us to meet and exceed the customers' satisfaction.

OCOM has been sticking to the quality system of ISO9001:2008. We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty. We have the mass production capabilities that produce thousands of printers and scanners a week. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

"Integrity based, Strive for excellence, Win-win cooperation". We would like establish stable and reliable partnerships with customers all over the world. OEM/ODM is welcome.

Contact us

Any queries, please contact us immediately, big supprise is waiting for you.

Sales Center:

Address: Unit 701, Block 14, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China;
Websites: http://www.possolution.com.cn ; http://www.ocominc.com ;
E-mail: ocom@ocominc.com , ocomtech@gmail.com ;
Skype: ocominc2000, ocominc;
MSN: ocomtech@hotmail.com, ocominc@hotmail.com;
Trademanager: szocominc, cn1500439666;
QQ: 2485890637,190852203;
Tel/Fax: +86.755.8605.3207.

Documents pertinents:

Voulez-vous en savoir plus? S'il vous plaît Cliquez ici.

spécification

Manuel de l'Utilisateur