

**200scan / sec haute balayage 32bit taux lecteur de code à barres  
(Modèle: OCBS-LA09)**

**Spécifications:**

<b>Caractéristiques de performance</b>	
Source de lumière:	650nm visible
Vitesse de balayage:	200 balayages par seconde
CPU	32 bits
Distance de lecture	2.5 ~ 600mm (100% UPC / EAN)
Largeur de numérisation	50mm @ 60mm, 220mm @ 200mm
Type de scanner:	Bi-directionnelle
Mode de fonctionnement	Auto Sense
Résolution:	3mil série haute résolution / série de champ 5mil longue de profondeur
Contraste d'impression minimum:	30%, la différence minimale de réflexion
Capacité de décodage:	UPC / EAN, UPC / EAN avec Supplementals, UCC / EAN 128, Code 39, Code 39 Full ASCII, code Trioptic 39, Code 128, Code 128 Full ASCII, Codabar, 2 parmi 5 entrelacé, discrète 2 de 5, Code 93, MSI, Code 11, RSS variantes, chinois 2 de 5, MSI / Plessey, UK / Plessey, UCC / EAN 128, le code chinois, GS1 DataBar (RSS) série
Angle de balayage	± 65 ° (inclinaison); ± 60 ° (hauteur); ± 42 ° (lacet)
<b>Caractéristiques physiques</b>	
Interfaces prises en charge:	PS2, RS232, USB pour l'option
Tension:	5V DC ± 5%
Actuel:	85 mA (en fonctionnement); 100 (max)
Indicateur	Beeper, LED
Matériel	ABS + PC
Se tenir debout	Avec
Dimensions:	156 * 68 * 83 mm (L * W * H)
Poids:	235g
Couleur:	Gris ou noir
<b>Environnement de l'utilisateur</b>	
Température de fonctionnement:	0 °C ~ 45 °C
Température de stockage:	-40 °C ~ 60 °C
Humidité:	5% à 90% (sans condensation)
Décharges électrostatiques:	Conforme à +/- 15KV évacuation de l'air et +/- 8KV de décharge de contact
Illumination ambiante	0 ~ 100 000 LUX
Déposez Spécifications:	Résiste à plusieurs chutes de 1,5 m à la surface du béton
Laser de classification	EN60825-1, classe 1



***Handheld Laser  
Barcode Scanner***

**OCBS-LA09**

**Product Picture**





## Features

**Simple but not easy**

200scan/sec high scan rate and long reading distance;





Excellent decode capability;



KBW, RS232 and USB supported;



Durable construction combined with future-proofing





Competitive price for 32bit model



## || All-round show





## Parameter

Performance Characteristics	
Light Source:	650nm visible
Scan Rate:	200 scans per second
CPU	32 bit
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Width of Scan	50mm@60mm, 220mm@200mm
Scanner Type:	Bi-directional
Operation mode	Auto Sense
Resolution:	3mil high resolution series / 5mil long depth field series
Print Contrast Minimum:	30%, minimum reflective difference
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar

	Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, chinese code , GS1 DataBar (RSS) series
Scanning Angle	±65°(tilt); ±60°(pitch); ±42°(yaw)
<b>Physical Characteristics</b>	
Interfaces Supported:	PS2, RS232, USB
Voltage:	5V DC±5%
Current:	85 mA (Operating); 100 (Max)
Indicator	Beeper, LED
Material	ABS+PC
Stand	Optional
Dimensions:	156*68*83 mm (L*W*H)
Weight:	235g
Color:	Grey and black
<b>User Environment</b>	
Operating Temperature:	0°C~45°C
Storage Temperature:	-40°C~60°C
Humidity:	5%-90% (non-condensing)
Electrostatic Discharge:	Conforms to +/-15KV air discharge and +/-8KV of contact discharge
Ambient Illumination	0 ~ 100,000 LUX
Drop Specifications:	Withstands multiple 1.5m drops to concrete surface
Laser classification	EN60825-1, class 1

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which



3. INTERNATIONAL AIR MAIL, usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com),  
Together we quest for the best.

