

2D Handheld Image Barcode Scanner

(M/N□OCBS-D016)

| Parameters | |
|--------------------------|---|
| Resolution | 640*480 256gray levels |
| Work mode | manual single scan, continuous scanning |
| Standard | 2m cable line |
| Light source | visible red light 630nm + 10nm |
| Data interface | USB, USB COM (virtual serial port) |
| Symbologies: 1D | Korea Post, China Post, TRIOPTIC,MSI/Plessey, UPC-A, UPC-E, EAN-8, EAN-13, ISBN, ISSN, ISBT, TELEPEN,UCC/EAN-128, Code 128, Code 11, Matrix 2 of 5, Interleaved 2 of 5,Industrial 2 of 5, Standard 2of 5, NEC 2 of 5, Code 39, Code 39 Full ASCII,Code 93,Codabar/NW7,UK/Plessey,TLC39, GS1 Databar (RSS) |
| 2D | PDF417, Micro PDF417, QR Code, Maxicode, Aztec, Code,Data Martix Code, HanXin Code, Codeblock F, Codeblock A |
| Reading depth | Code 39 (5MIL):50mm~120mm UPC/EAN (13mil):20mm~320mm Data Matrix (7.5mil):63mm~150mm PDF417 (6.6mil):62mm~145mm |
| Scan angle | 45 degrees (level), 30 degrees (vertical) |
| Alarm mode | buzzer voice prompts, LED lights |
| Physical parameters | |
| Specification | 182*65*109mm (L*W*H) |
| Weight | 195g (without bracket) |
| Cable line standard | more than 2m |
| Appearance material: | ABS+PC flame retardant materials |
| DC power supply voltage | +5V + 5% |
| Standby current | 40mA |
| Environmental parameters | |
| Working temperature | -20 C ~ 60 C |
| Storage temperature | -30 C ~ 70 C |
| Relative humidity | 0% ~ 95% (no condensation) |
| Ambient illumination | normal indoor and outdoor direct sunlight |
| Package level | IP54 sealing air dust particles resist invasion |
| Certification | by CE, FCC and ROHS certification |