

Scanner tenu dans la main de longue distance de laser de la distance 2d de la transmission 433Mhz BarCode

Aiming Light Source	617 nm LED
Lighting Light Source	625 nm LED
Scanning Angle	39° (H) x 25° (V)
Rotation Angle	0 - 360°
Elevation Angle	± 65°
Tilt Angle	± 60°
Print Contrast	Higher than 25%
1D	UPC/EAN, UPC/EAN with <u>supplementals</u> , <u>BooklandEAN</u> , ISSN, UCC Coupon Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, <u>Trioptic Code 39</u> , Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2of 5, <u>Codabar</u> , MSI, Chinese 2 of 5, GS1 Data <u>Barvariants</u> , Korean 3 of 5, ISBT <u>Concat</u>
2D	PDF417, MicroPDF417, Composite Codes, TLC-39,Data Matrix, <u>Maxicode</u> , QR Code, <u>MicroQR</u> , Aztec
Interface	USB (<u>Wireless receiver cable</u>)
Communication distance	433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside:20m (Max)
Operating Temperature	-10 deg C - 45 deg C
Storage Temperature	-20 deg C - 65 deg C
Operating Humidity	5%-85%
Storage Humidity	5%-95%
Durability	Withstands multiple 1.5m drops to concrete
Input Power	DC 5V, 280mA
Charging time	6h