Android bluetooth mobile thermal printer (OCPP-M05)

Specifications:

| Dimensions (W × D × H) | 105 × 75 × 45mm | |
|------------------------|---|--|
| Weight | 134 g | |
| Color | Black | |
| Effective print width | 48 mm | |
| Printing method | Thermal Line Printing | |
| Print command | ESC / POS compatible instruction set | |
| Print speed | To 90mm/sec | |
| Resolution | 8 dots / mm (203DPI) | |
| Print Font | In 12X24 / 24x24 in | |
| Column capacity | 32 / 16columns | |
| Character size | 1.5×3.0 mm (width x height) / $3.0x3.0$ mm (width x height) | |
| Paper Size | Diameter of 58.0 mm to ± 0.1mm x40.0 | |
| Paper Thickness | 0.06 to 0.08 mm | |
| Character set | Alphanumeric / Chinese Text | |
| Interface | USB, RS-232,Bluetooth (optional) | |
| Flash | 256KB | |
| Power Adapter | 9V DC/2A | |
| Battery Power | The DC / 1500 mA 7.4V; battery can stay in 4-5 days, when it is full of strength, it can print 120-150M Paper | |
| Other Features | Paper detection, power detection, manually shut down | |
| Working conditions | Temperature: -10Celsius~50CelsiusHumidity: 10%~90% | |
| Storage conditions | Temperature: -20Celsius~70CelsiusHumidity: 5%~95% | |
| Device Name | Can be customized to select letters and numbers up to 30 ASCII characters. | |
| Password | Default Input pairing code "1234"It can be customized. Maximum 6 digitals. | |
| Size of the power plug | 3.5 * 1.1 mm | |

| | P/N | Description |
|----------------------|----------------|---|
| | ОСРР-М05-ВВ | With Bluethooth and battery,supprot Android |
| | OCPP-M05-BB-AI | With Bluethooth and battery,supprot Android and IOS |
| | OCPP-M05-UB | With Barrery USB Communication, |
| Ordering information | OCPP-M05-U | USB Communication, without BT, Battery |
| | ОСРР-М05-В | Blutooth Communication, without Battery |
| | OCPP-M05-UC | USB Communication,with Car Charger |
| | OCPP-M05-BC | Bluetooth Communication with Car Charger |
| | OCPP-M05-C | Other Customized |