Handheld lecteur de codes barres laser avec support

(Modèle: OCBS-LA06)

Caractéristique:

1.Auto-induction intégrée, conception verte;

2.High vitesse de balayage et de longue distance de lecture;

3.Excellent décoder la capacité;

4.KBW, RS232 et USB pris en charge;

Construction 5.Durable combiné avec l'avenir épreuvage;

Un cahier des charges:

Caractéristiques de performance	
Source de lumière:	Laser visible (650-670nm)
Taux de numérisation:	100 balayages par seconde
Distance de lecture	2.5 ~ 600mm (100% UPC / EAN)
Type de scanner:	Bi-directional
Résolution:	0.10mm (4mil) PCS 0.9
Contraste d'impression minimum:	20%, la différence minimale de réflexion (@ 650nm)
Capacité de décodage:	UPC / EAN, UPC / EAN avec Supplementals, UCC / EAN128, Code 39, Code 39 pleine ASCII, le code 39 Trioptic, le code 128, le code ASCII 128 complète, codabar, 2 parmi 5 entrelacé, discrète 2 de 5, Code 93, MSI, le code 11, ATA, RSS variantes, 2 5 chinois ...
Caractéristiques physiques	
Interfaces prises en charge:	PS2, RS232, USB
Tension:	DC + 5V +/- 5%
Actuel:	100 mA
Courant de repos:	& lt; 40 mA
Source d'énergie:	Puissance hôte ou (RS232) alimentation externe
Angle de balayage	Inclinaison 45 ° 60 ° d'élévation
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Poids:	140g (sans support)
Supporter	Avec
Couleur:	Ivoire et noir
Environnement de l'utilisateur	
Température de fonctionnement:	0 ℃ ~ 50 ℃
Température de stockage:	-40 ℃ ~ 70 ℃
Humidité:	5 ~ 95% d'humidité relative, sans condensation
Décharge électrostatique:	Confirmer à +/- 15KV évacuation de l'air et de +/- 8 kV décharge de contact
Déposez Spécifications:	Résiste 1.5m multiples chutes sur béton

Sûr:	
EMI / RFI:	FCC Classe A et CE
Sécurité du laser:	2 produits laser de classe CDRH

Product Picture

Features

High scan rate and long reading

High scan rate and long reading distance

Excellent decode capability

KBW, RS232 and USB supported

www.ocominc.com

Durable construction combined with future-proofing

All-round show

www.ocominc.com

Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165.42mm X W69.72mm X H89.67mm
Weight:	140g (without stand)
Stand	With
Color:	Ivory and black
User Environment	
Operating Temperature:	0℃~50℃
Storage Temperature:	-40℃~ 70℃
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

www.ocominc.com

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.