

OCBP-M1001 thermique code à barres USB fabricant d'étiquettes de rouleau

| | |
|--------------------------|---|
| Printing Method | Thermal Line |
| Printing Speed | 80mm/s (Thermal Paper) |
| | 70mm/s (Label Sticker) |
| Resolution | 8 dots/mm |
| Effective Printing Width | 100mm/72mm/48mm/37.5mm |
| Character Set | ASCII, GB18030 (Chinese), BIG5, <u>Codepage</u> |
| Print Font | Font A: 12*24; Font B: 8*16 |
| Self-defined Character | Yes |
| Paper Type | Thermal paper/Label Paper |
| Paper Roll Diameter | 40mm (max.) |
| Roll Core Inner Diameter | 13mm(min.) |
| Paper Thickness | 0.06~0.16mm |
| Paper Supply Method | Drop-in easy paper loading |
| TPH | 50km |
| <u>Barcode</u> | 1D: EAN-13, EAN-8, <u>UPC-A</u> , <u>UPC-E</u> , CODE39, CODE93, CODE128, CODABAR, INTERLEAVED 25 |
| | 2D: PDF417、QRCODE、DATA Matrix |
| Emulation | CPCL/ <u>ESC-POS</u> |
| Driver | Windows 98 / ME / 2000 / NT / XP / 2003 Server/Vista/Win7/Win 8/Win10 |
| Sensor | Paper End Sensor, Black Mark, Label Interval |
| Interface | USB/Bluetooth |
| Button | Power, Feed, Mode |
| Indicator | Power, Feed, Mode |