Scanner de code à barres à balayage automatique pour 1D / 2D avec port USB ou série (M / N .: OCBS -2008)

Principale Fonctionnalité:

Technologie d'imagerie haute performance;
Balayage omnidirectionnel, facile à numériser;
Peut lire le code à barres sur l'écran et le code à barres de couleur;
4mil excellente précision de numérisation;
Multi fonction fonction spéciale prise en charge;
Interfaces multiples en option
Stand pour l'option.

Caractéristiques de performance:

Fonction		
Source de lumière		LED blanche
Bip		Prise en charge
Supporter		Optionnel
Indicateur		LED verte, bip
Performances d'analyse		
Capteur		CMOS
Résolution		640 * 480,256 niveaux de gris
Vitesse de décodage maximale		13 UPC 40 cm / s
Angle de lecture		horizontalement à 50 degrés; verticalement 20 degrés
Précision		≥4mil
Capacité de décodage	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (EAN Bookland), ISSN, Code 39, Code 39 complet ASCII, Code 32, Code trioptique 39, Entrelacé 2 sur 5, Industriel 2 de 5 (discret 2 sur 5), matrice 2 sur 5, Codabar (NW7), code 128, UCC / EAN 128 (GS1-128), ISBT 128, code 93, code 11 (USD-8), MSI / Plessey
	2D	PDF417, MicroPDF417, code QR, DataMatrix, code Han Xin, code aztèque, GS1 Com pos ite
Profondeur de champ		Code 39 (5mil): 50mm ~ 120mm Code 39 (10mil): 25mm ~ 250mm UPC / EAN (13mil): 20mm ~ 320mm Data Matrix (7.5mil): 63mm ~ 150mm PDF417 (6.6mil): 62mm ~ 145mm
Sensibilité		Inclinaison ± 45 ° @ 0 ° Rouleau et 0 ° Inclinaison Rotation ± 30 ° à 0 ° Pas et 0 ° Inclinaison Déviation ± 45 ° @ 0 ° Rouleau et 0 ° Inclinaison
Électrique		
Interface		USB, USB COM (port série virtuel)
Tension d'entrée		3.3v ~ 5v DC
Puissance standard		2,0w (400mA)
Maximum d'énergie		2.5w (450mA)
Adaptateur DC		Max 5.5V 1A
LED CLASS		Classe I
Test EMC		FCC part15, IEC60825-1, EN55022 classe B
Environnement utilisateur		
Faire fonctionner la température		-20 ° C ~ +60 ° C (-4 ° F à 144 ° F)
Température de stockage		-30 ° C ~ +70 ° C (-22 ° F à 158 ° F)
Humidité		5% - 95% (sans condensation)
Résistance à la chute:		1,5 m (5,0 pi) de gouttes de béton
Classe IP		IP54
Intensité lumineuse		Travail: feux de soleil, lampes fluorescentes
Physique		
Dimensions		156 * 68 * 83mm

Poids	195 g (sans support)
Dimension du paquet	48 * 36 * 47CM (20pcs avec stand 13.5KG)
	48 * 39 * 52CM (30pcs sans support 15KG)

Handheld Image Scanner

for1D/2D Barcode

OCBS-2008

Product Picture

Features

Reliable with good price

High performance imaging technology;
Omni-directional scanning, easy to scan;

4mil excellent scanning accuracy ;
Can read the barcode on the screen
and color barcode;

Multi special function setting supported;
SDK/API Available;

Multi interfaces optional;
Stand for option.

Application place

Bookstore

Supermakte

Pharmacy

Warehouse

Restaurant

Clothing store

Parameter

Function		
Light source		White LED
Beep		Supported
Stand		Optional
Indicator		Green LED, beep
Scan performance		
Sensor		CMOS
Resolution		640*480,256 gray levels
Maximum decoding speed		13mil UPC 40cm/s
Reading angle		horizontally 50 deg; vertically 20 Deg
Precision		≥4mil
Decode capability	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128 (GS1-128), ISBT 128, Code93, Code 11 (USD-8), MSI/Plessey
	2D	PDF417, MicroPDF417, QR Code, DataMatrix, Han Xin Code, Aztec Code, GS1 Composite
Depth of field		Code 39(5mil): 50mm~120mm Code 39(10mil): 25mm~250mm UPC/EAN (13mil): 20mm~320mm Data Matrix(7.5mil): 63mm~150mm PDF417(6.6mil): 62mm~145mm
Sensitivity		Inclination ±45° @0°Roll and 0°Skew Rotation ±30° @0°Pitch and 0°Skew Deflection ±45° @0°Roll and 0°Skew
Electrical		
Interface		USB,USB COM(virtual serial port)
Input Voltage		3.3v~5v DC
Standard Power		2.0w (400mA)
Max Power		2.5w (450mA)
DC adapter		Max 5.5V 1A
LED CLASS		Class I
EMC Test		FCC part15,IEC60825-1,EN55022 Class B
User Environment		
Operate Temperature		-20 deg C ~ +60 deg C (-4 Deg F to 144 deg F)
Storage Temperature		-30 deg C ~ +70 Deg C (-22 Deg F to 158 deg F)
Humidity		5% - 95%(non- condensation)
Drop resistance:		1.5m (5.0ft) drops to concrete
IP class		IP54
Light intensity		Working: sun lights, fluorescent lights
Physical		
Dimensions		156*68*83mm
Weight		195 g (without stand)
Package dimension		48*36*47CM (20pcs with stand 13.5KG)
		48*39*52CM (30pcs without stand 15KG)

Production Capacity:

✓ Indicates information has been verified onsite by a certification specialist

Production Capacity

Verified	Product Name	Production Line Capacity	Actual Units Produced(Previous Year)
✓	Thermal Printer	40,000 Sets / Month	250,000 Sets
✓	Dot Matrix Printer	15,000 Sets / Month	10,000 Sets
✓	Bluetooth Printer	30,000 Sets / Month	20,000 Sets
✓	Barcode Scanner	40,000 Sets / Month	20,000 Sets
✓	POS Machine	5,000 Sets / Month	10,000 Sets
✓	Magnetic Card Reader and Writer	45,000 Sets / Month	50,000 Sets

Verified by TUV on 2013.7.15

Quality Assurance:

OCOM is dedicated to providing most cost-effective products and services with highest quality that will meet customers' satisfaction.
Since the establishment, OCOM has been sticking strictly to the standard and requirements of ISO9001: 2000 in the processes of research, design, manufacturing and services.
OCOM's products have passed CE, FCC, TUV, RoHs and other certifications.
We make strictly IQC, IPQC and OQC inspection per industrial standard. All the products must pass 24-48 hours aging test before shipment. Some designated models can have as long as 24 months warranty.

Test Equipments:

✓ Indicates information has been verified onsite by a certification specialist

Test Equipment and Facilities

Verified	Machine Name	Brand & Model No.	Quantity
✓	Ageing Tester	No Information	6
✓	Withstand Voltage Tester	CC2670A	1
✓	Oscilloscope	TBS1102	1
✓	DC Power Supply	PS-305DM	6
✓	Digital Torque Meter	HP100	1
✓	Calliper	GUANGLU	2
✓	Multi-meter	VC890D	7
✓	Test Computer	No Information	13

Verified by TUV on 2013.7.15

Certification:

Warranty and After Sales:

- All products' warranty are not less than 12 month, some models even up to 24 months warranty.
- Spare parts will be provided for mass orders for customers' local maintenance.
- Any product found to be defective within 30 days of shipment shall be deemed Dead on Arrival (DOA). DOA products will be advance replaced and shipped via express.
- Have distributors or authorized agents in the main market who can provide local repair and replacement services.
- Professional CRM management insures fast respond for customer's enquiries and orders tracking.
- Sales with many years experience in foreign trade, proficient in foreign languages and strong sense of responsibility.
- 7*24 hours online, responds with 12 hours in working days, and within 24 hours for rest days.

Packing and Shipment:



Payment:

secure payment

AliExpress PayPal Trade Assurance

Customers Reference

Over the years, OCOM keep efforts on marking "OCOM" as an internationally recognized brand, and we have estabilshed goods relationship with our customers and have friendly communication with each other.

Company Profile

OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers , Thermal Printer, Barcode printer,Dot Matrix Printer， Barcode Scanner, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT, products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.

Monica Fu

OCOM Technologies Limited

Add: 4/F, Block10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China
Tel: 0086.755.8605.3207 ext 801
Fax: 0086.755.8605.3207 ext 868
Web: www.ocominc.com
E-mail: sales01@ocominc.com, sales01@ocomtech.com.cn
Skype: ocomsales01; **MSN**: ocomsales01@hotmail.com
Ali TM: cn1001868228; **QQ**: 1483705401
Mobile/Wechat/Whatsapp: 0086.189 4871 3992

Reliable One-Stop Supplier for POS and Auto-ID Related Products