

OCBS -LA11 Scanner tenu dans la main tenu dans la main automatique de code barres d'USB avec le support

(Modèle: OCBS -LA11)

CARACTÉRISTIQUES:

Caractéristiques de performance	
Source de lumière:	Laser visible (650-670nm)
Taux de balayage:	100 balayages par seconde
Distance de lecture	2.5 ~ 600mm (100% UPC / EAN)
Type de scanner:	Bi-directionnel
Résolution:	0.10mm (4mil) à PCS 0.9
Contraste d'impression minimum:	30%, différence minimale de réflexion (@ 650nm)
Taux d'erreur:	1/3000000
Capacité de décodage:	UPC / EAN, UPC / EAN avec suppléments, UCC / EAN128, code 39, code 39 ASCII complet, code 39 trioptique, code 128, code 128 ASCII complet, codabar, entrelacé 2 sur 5, discret 2 sur 5, code 93, MSI , code 11, ATA, RSS variantes, chinois 2 sur 5 ...
Caractéristiques physiques	
Interfaces supportées:	PS2, RS232, USB
Tension:	DC + 5 V +/- 5%
Actuel:	100 mA
Courant inactif:	& lt; 40 mA
Source d'énergie:	Alimentation hôte ou alimentation externe (RS232)
Angle de lecture	Inclinaison 45 ° Altitude 60 °
Dimensions:	L165mm X W63mm X H87mm
Poids:	129g (sans support)
Supporter	Optionnel
Couleur:	Gris et noir
Environnement de l'utilisateur	
Température de fonctionnement:	0 °C ~ 40 °C
Température de stockage:	-40 °C ~ 60 °C
Humidité:	5 ~ 95% d'humidité relative, sans condensation
Décharge électrostatique:	Confirmer à +/- 15KV décharge d'air et +/- 8KV de décharge de contact
Spécifications de chute:	Résiste à plusieurs gouttes de 1,5 m de béton
Sûr:	
EMI / RFI:	FCC Classe A et CE
Sécurité laser:	Produit laser CDRH classe 2

Détails du produit:



ocom
All your side

*Handheld Laser
Barcode Scanner*

OCBS-LA11

Product Picture





Features

Simple but not easy

Handheld laser barcode scanner with auto sense function;



Flexible operation with 360 degree



rotation metal stand;



High scan rate (100 scans/sec) and long reading distance;



Excellent decode capability;





KBW, RS232 and USB supported;



|| All-round show





Parameter

Performance Characteristics	
Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance:	2.5 ~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.9
Print Contrast Minimum:	30%, minimum reflective difference (@650nm)
Error Rate:	1/3000000
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5...

Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB
Voltage:	DC+5V+/-5%
Current:	100 mA
Idle Current:	<40 mA
Power Source:	Host power or external (RS232) power supply
Scanning Angle	Inclination 45° Elevation 60°
Dimensions:	L165mm X W63mm X H87mm
Weight:	129g (without stand)
Stand	Optional
Color:	Grey and black
User Environment	
Operating Temperature:	0°C~40°C
Storage Temperature:	-40°C~ 60°C
Humidity:	5~95% relative humidity, non-condensing
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge
Drop Specifications:	Withstands multiple 1.5m drops to concrete
Safe:	
EMI/RFI:	FCC Class A and CE
Laser Safety:	CDRH class 2 laser product

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port

5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.

