

Chine bureau mains libres USB filaire 1d & 2d qr code scanner de codes à barres omnidirectionnel pour supermarché

(M/N :OCBS-T215)

Traits:



Grande fenêtre de lecture ;

Identifiez rapidement le code 1D/2D de l'écran ;

Prise de câble de données cachée anti-traction.

spécification

Général	
Modèle	OCBS-T215
Interface	USB
Tension de fonctionnement	5V
Courant de démarrage	420mA
Travail en cours	400mA
Courant de veille	270mA
Performance	
Capteur	Exposition globale 640*480 capteur CMOS
Source de lumière	DEL rouge
Vue sur le terrain	57,2° (H), 44,2° (V)
Tolérance de mouvement	> 0.3m/s
Angle de balayage	Pas ±70°@ 0°Roll et 0° Skew Roulis 360° @ 0° Pitch et 0° Skew Incliner ±70°@ 0°Roll et 0° Pitch
Contraste des symboles	Différence de réflexion minimale de 20 %
Immunité à la lumière ambiante	0-100 000 Lux
Profondeur de champ typique	Code39(5mil):20mm-80mm, EAN13(13mil):10mm-160mm QR(15mil):10mm-140mm Matrice de données (15mil):10mm-100mm PDF417 (10mil):10mm-120mm
Capacité de décodage	(Codabar),(Code 39),(Code 32),(Industriel 2 sur 5),(Entrelacé 2 sur 5),(Standard 2 sur 5),(Matrice 2 sur 5),(Code 93),(Code 11),(Code 128),(UPC-A),(UPC-E),(EAN/JAN-8),(EAN/JAN-13),(GS1 DataBar(RSS14)(PDF417),(Code QR),(Micro QR),(Data Matrix),(Aztèque),(Code Hanxi)
Physique	
Lester	Brut : 640 g
Forfait	230*170*95mm
Environnement	
Température et humidité de travail	0 à 45 degrés centigrades, 10 % ~ 80 % sans condensation
Température et humidité de stockage	-20 à 60 degrés centigrades, 10 % ~ 90 % sans condensation















Model: OCBS-T215

Interface: USB



OCBST2152214100001

Made in China





Section	Page	Description
1	1	Introduction
2	2	Safety Information
3	3	Special Precautions
4	4	General Information

1. Safety Information

1.1. The safety and health of the user are the primary concern of the manufacturer. Please read the instructions carefully and follow them exactly to avoid any risk of injury or damage to the device.

1.2. The device should only be operated with a clean, well-ventilated area. A small amount of dust may be added to the device, and this should be cleaned regularly.

Special Precautions: This instruction does not describe and cannot be used for the installation and wiring of the device. The user must refer to the manufacturer's instructions for the correct installation and wiring of the device. The user must also refer to the manufacturer's instructions for the correct use of the device.

2. GENERAL INFORMATION



Information: This device is a power supply unit. It is not intended for use as a power source for other devices. It is not intended for use in a hazardous environment. It is not intended for use in a location where it may be exposed to fire or other hazards. It is not intended for use in a location where it may be exposed to moisture or other environmental conditions. It is not intended for use in a location where it may be exposed to vibration or other mechanical stress. It is not intended for use in a location where it may be exposed to electromagnetic interference. It is not intended for use in a location where it may be exposed to radio frequency interference. It is not intended for use in a location where it may be exposed to high temperatures. It is not intended for use in a location where it may be exposed to high humidity. It is not intended for use in a location where it may be exposed to high pressure. It is not intended for use in a location where it may be exposed to high altitude. It is not intended for use in a location where it may be exposed to high speed winds. It is not intended for use in a location where it may be exposed to high speed vibrations. It is not intended for use in a location where it may be exposed to high speed impacts. It is not intended for use in a location where it may be exposed to high speed collisions. It is not intended for use in a location where it may be exposed to high speed explosions. It is not intended for use in a location where it may be exposed to high speed fires. It is not intended for use in a location where it may be exposed to high speed explosions. It is not intended for use in a location where it may be exposed to high speed fires.





2D Barcode Scanner
Model: OCBS-T215 Color: Black
Interface: USB CE FC
Power Input: 5V1A
OCBS T2152214100001
Made in China