

Supermarché 360 degrés bureau usb Windows Android robuste 1d  
2d scanner de codes à barres omnidirectionnel

(M/N :OCBS-T215)

Traits:



Grande fenêtre de lecture ;

Identifiez rapidement le code 1D/2D de l'écran ;

Prise de câble de données cachée anti-traction.

## spécification

<b>Général</b>	
Modèle	OCBS-T215
Interface	USB
Tension de fonctionnement	5V
Courant de démarrage	420mA
Travail en cours	400mA
Courant de veille	270mA
<b>Performance</b>	
Capteur	Exposition globale 640*480 capteur CMOS
Source de lumière	DEL rouge
Vue sur le terrain	57,2°(H), 44,2°(V)
Tolérance de mouvement	> 0,3 m/s
Angle de balayage	Pas $\pm 70^\circ$ @ $0^\circ$ Roll et $0^\circ$ Skew Roulis $360^\circ$ @ $0^\circ$ Pitch et $0^\circ$ Skew Incliner $\pm 70^\circ$ @ $0^\circ$ Roll et $0^\circ$ Pitch
Contraste des symboles	Différence de réflexion minimale de 20 %
Immunité à la lumière ambiante	0-100 000 Lux
Profondeur de champ typique	Code39(5mil):20mm-80mm, EAN13(13mil):10mm-160mm QR(15mil):10mm-140mm Matrice de données (15mil):10mm-100mm PDF417 (10mil):10mm-120mm
Capacité de décodage	(Codabar), (Code 39), (Code 32), (Industriel 2 sur 5), (Entrelacé 2 sur 5), (Standard 2 sur 5), (Matrice 2 sur 5), (Code 93), (Code 11 ),(Code 128),(UPC-A),(UPC-E),(EAN/JAN-8),(EAN/JAN-13),(GS1 DataBar(RSS14) (PDF417), (Code QR), (Micro QR), (Data Matrix), (Aztèque), (Code Hanxi)
<b>Physique</b>	
Lester	Brut : 640 g
Forfait	230*170*95mm
<b>Environnement</b>	
Température et humidité de travail	0 à 45 degrés centigrades, 10 % ~ 80 % sans condensation
Température et humidité de stockage	-20 à 60 degrés centigrades, 10 % ~ 90 % sans condensation

















Model: OCBS-T215

Interface: USB



OCBST2152214100001

Made in China





1. Introduction	1
2. Safety Precautions	2
3. Operation	3
4. Troubleshooting	4
5. Appendix	5

**Special Precautions Manual**

1. The safety and health of the operating member should be the first priority. When handling electrical equipment, please refer to the safety signs and the following items.

2. The equipment shall not be repaired with a cover with which a small amount of leakage can be added to the inner, and there is a risk of electric shock.

**Special Precautions:** This equipment has been strictly and carefully checked and confirmed, but it still does not exclude the occurrence of errors or sparking and breakdowns. When unnecessary, please do not connect or disassemble the equipment without referring to the copyright of this technology to protect the copyright, and we will not be held responsible for any damage.

**FOR POWER SUPPLY TO A POWER SUPPLY**



Copyright © 2010 by OCOM. All rights reserved. This document is a confidential document. It is not to be distributed, copied, or reproduced without the prior written consent of OCOM. OCOM is not responsible for any damage or loss of data caused by the use of this equipment. OCOM is not responsible for any damage or loss of data caused by the use of this equipment. OCOM is not responsible for any damage or loss of data caused by the use of this equipment.





**2D Barcode Scanner**  
Model: OCBS-T215      Color: Black  
Interface: USB  
Power Input: 5V1A      CE FC  
  
OCBS T2152214100001  
Made in China