

Haute qualité 433 MHz ou Bluetooth sans fil QR code 2D Barcode scanner avec berceau

Modèle: COEC-W231-4/b

Caractéristiques:

- 1, 433 MHz distance de communication sans fil extérieure 300 m, 100 m intérieure; Distance de communication sans fil Bluetooth extérieure 20 m, et 10 m intérieur;
- 2, équipé de la communication et de la base de charge
- 3, la couverture en plastique molle pour protéger l'objectif et le contour améliore considérablement la performance anti-Drop;
- 4, code-barres sur l'écran des ordinateurs et des téléphones portables peuvent être numérisés;
- 5, aucun conducteur de besoin, plug and Play;
- 6, peut stocker plus de 10 000 morceaux de données;
- 7, plusieurs scanners peuvent être connectés à un récepteur (433 MHz).

Paramètres:

| | |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Source lumineuse de visée | 617 nm LED |
| Source lumineuse d'éclairage | 625 nm LED |
| Angle de balayage | 39 ° (h) x 25 ° (v) |
| Angle de rotation | 0-360 n° |
| Angle d'élévation | ± 65 ° |
| Angle d'inclinaison | ± 60 ° |
| Contraste d'impression | Supérieur à 25% |
| 1D | UPC/EAN, UPC/EAN avec suppléments, BooklandEAN, ISSN, UCC coupon Extended code, Code128, GS1-128, ISBT 128, code 39, code 39 Full ASCII, code trioptique 39, code 32, Code 93, code, Matrix 2 de 5, Interleaved 2 of 5, discret 2 5, Codabar, MSI, chinois 2 de 5, GS1 Data Barvariants, coréen 3 de 5, ISBT Concat |
| 2D | PDF417, MicroPDF417, codes composites, TLC-39, Data Matrix, MaxiCode, QR code, MicroQR, Aztec |
| Interface | USB (câble récepteur wireless) |
| Distance de communication | 433 MHz: intérieur: 100 m; Extérieur: 300 m (max.) Bluetooth: intérieur: 10 m; Extérieur: 20 m (max.) |
| Température de fonctionnement | -10 deg c-45 deg c |
| Température de stockage | -20 deg c-65 deg c |
| Humidité de fonctionnement | 5%-85% |
| Humidité de stockage | 5%-95% |
| Durabilité | Résiste à plusieurs gouttes de 1,5 m au béton |
| Puissance d'entrée | C.c 5V, 280mA |
| Temps de charge | 6 |
| Batterie | 1500mAh |
| Lumination | Intérieur: 3,000 lux Max; Lumière du soleil extérieure: 86000LUX Max |

| | | | |
|-------------------------------------|-----------------------------------------------------------------------------|----------------------------|------|
| Qualité IP | IP42 | | |
| Plages de décodage | | | |
| Performances typiques * | | Gammes de travail typiques | |
| | | Gamme HD Focus | |
| Type de code à barres | Densité de symbole | Près | Loin |
| Code 39 | 5,0 mil | mm | 90 |
| 100% UPCA | 13,0 mil | 8 | 200 |
| Code 39 | 20,0 mil | 8 | 250 |
| PDF 417 | 6,8 mil | mm | 95 |
| Matrice de données | 10,0 mil | mm | 110 |
| Code QR | 20,0 mil | 10 | 150 |
| Résolution 1D Code 39 | 4 mil | | |
| Matrice de données 2D de résolution | 10 mil | | |
| Matériel | ABS + PC | | |
| Dimension | Scanner (70 * 95 * 168) base (145 * 112 * mm) | | |
| Poids net | Scanner 185 base 186 | | |
| Informations de commande: | COEC-W231-4: Scanner de code-barres 2D sans fil 433 MHz avec berceau | | |
| | COEC-W231-b: Scanner barocde 2D Bluetooth avec berceau | | |



FIVE CORE STRENGTHS

HIGH SPEED SCANNING EFFICIENCY OF CHOICE



LONG DISTANCE WIRELESS COMMUNICATION



STRONG DECODING ABILITY



CHARGING CRADLE



STABLE STRUCTURE



NO NEED DRIVER, PLUG AND PLAY

1

FAST SCAN,HIGH RECOGNITION RATE



2

STRONG DECODING ABILITY



3

CRADLE FOR CHARGING AND WIRELESS COMMUNICATION



4

STABLE STRUCTURE, DURABLE AND HIGH RUB RESISTANCE



5

NO NEED DRIVER PLUG AND PLAY



THE PRODUCT FAMILY



PRODUCT PACKAGING FIGURE



WIDE RANGE OF APPLICATION, RICH TYPE OF DECODING

IT'S APPLICATED AT ANY PLACE, THE MORE AND MORE CUSTOMERS TREND TO USE OCOM SCANNER



**PRODUCT
INFORMATION**

| | |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Aiming Light Source | 617 nm LED |
| Lighting Light Source | 625 nm LED |
| Scanning Angle | 39° (H) x 25° (V) |
| Rotation Angle | 0 - 360° |
| Elevation Angle | ± 65° |
| Tilt Angle | ± 60° |
| Print Contrast | Higher than 25% |
| 1D | UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coupon Extended Code, Code 128, GS1-128, ISBT 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 32, Code 93, Code 11, Matrix 2 of 5, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Bar variants, Korean 3 of 5, ISBT Concat |
| 2D | PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxicode, QR Code, MicroQR, Aztec |
| Interface | USB (Wireless receiver cable) |
| Communication distance | 433mhz: Inside: 100m; Outside: 300m (Max) Bluetooth: Inside: 10m; Outside: 20m (Max) |
| Operating Temperature | -10 deg C - 45 deg C |
| Storage Temperature | -20 deg C - 65 deg C |
| Operating Humidity | 5%-85% |
| Storage Humidity | 5%-95% |
| Durability | Withstands multiple 1.5m drops to concrete |
| Input Power | DC 5V, 280mA |
| Charging time | 6h |
| Battery | 1500mAh |
| Lumination | Inside: 3.000 LUX max; Outside sunlight: 86000LUX max |
| IP Grade | IP42 |

| DECODE RANGES | | | |
|---------------------------|---------------------------------------------|------------------------|-------|
| Typical Performance* | | Typical Working Ranges | |
| | | HD Focus Range | |
| Bar Code Type | Symbol Density | Near | Far |
| Code 39 | 5.0 mil | 5mm | 90mm |
| 100% UPCA | 13.0 mil | 8mm | 200mm |
| Code 39 | 20.0 mil | 8mm | 250mm |
| PDF 417 | 6.8 mil | 5mm | 95mm |
| Data Matrix | 10.0 mil | 5mm | 110mm |
| QR Code | 20.0 mil | 10mm | 150mm |
| Resolution 1D Code 39 | 4 mil | | |
| Resolution 2D Data Matrix | 10 mil | | |
| Material | ABS+PC | | |
| Dimension | Scanner (70*95*168mm) Base (145*112*74mm) | | |
| Net Weight | Scanner 185g Base 186g | | |
| Ordering Info. | 433MHz wireless communication (OCBS-W231-4) | | |
| | Bluetooth communication (OCBS-W231-B) | | |

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.



Contact us

Any queries, please contact us immediately, big surprise is waiting for you.

Sales Center:

Address: 4/F, Block 10, Zhongxing Industrial Park, Chuangye Road, Nanshan District, Shenzhen 518054, China

Website: www.ocominc.com www.possolution.com.cn;

E-mail: sales15@ocominc.com

Tel: 0086.755.86053207-815;

Fax: 0086.755.86053207-868;

QQ: 210852908;

Wechat: [ocomsales15](#);

Whatsapp: +0086.189.4879.9080;

ocominc.com

ocominc