


COEC-W232 USB Bluetooth Wireless Barcode scanner

| PHYSICAL CHARACTERISTICS | |
|--------------------------------|--|
| Light Source | Visible Laser Diode (VLD) @ 650 nm |
| scanner Dimensions(W * H * D) | 168*72*93 mm |
| receiver Dimensions(W * H * D) | 130*75*129mm |
| Material | ABS+TPU /Aluminium alloy |
| scanner Weight | 190g (Including battery) |
| receiver Weight | 180g |
| User Mode | Hand-held |
| Scanning Mode | Manual/ Automatic |
| Indicator Light | Scanner LED Red and Blue receiver Left Green+ right Blue |
| Buzzer | Buzzer Volume Adjustable |

| PERFORMANCE CHARACTERISTICS | |
|-----------------------------|---|
| Width of Scan Field | 60mm@30mm (From engine face) 98mm@100mm (from engine face) |
| Depth of Scan Field | 10-450mm (Contrast 0.9 Density0.25) |
| Scan Speed | 300 scans/sec |
| Scan Precision | 0.10-0.825mm |
| Bit Error Rate | 1/(5million) |
| Symbologies Supported | 1D UPC-A, UPC-E, EAN-8, EAN-13 Code 39, Code 32, Coda bar ,Code 128, ISBT 128, Code 93, Interleaved 2 of 5 Discrete 2 of 5 ,CODE11, MSI,  名称sey GS1-DataBar, UCC/EAN-128,BooklandEAN, Bookland EAN/ISBN , Trioptic Code39, CouponCodeGS1, DataBar-14, SETUP128 GS1Data Bar Limited, GS1Data Bar Expanded, RSS |
| | 2D PDF417 DataMatrix(DM) QR |
| Battery | 3.7V/1200mAh,Li-ion |
| Charge Time | 2.5 Hours |
| Scan Time | 10 Hours |
| Scan Current | 95mA |
| Standby current | 25mA |
| Maximum Pitch Angles | 60° |
| Maximum Tilt Angles | 45° |
| Working Frequency | 433MHz |
| Communication Distance | 200m (Open Places) |
| Flash | 16MB |
| Communication Interface | USB |