

# OCBS-W800 433MHz codes à barres sans fil de poche scanner 32 bits

## CARACTÉRISTIQUES:

characterstics PHYSIQUES	
Source de lumière:	Diode Laser Visible (VLD) @ 650 nm
Scanner Dimensions :	168mm * 72mm * 93mm (W * H * D)
Dimensions du récepteur:	130mm * 45mm * 129mm (W * H * D)
Matériel:	ABS + TPR / alliage d'aluminium
Poids:	370g
Mode de numérisation:	À main; Mode balayage continu.
Voyant:	LED rouge et bleu
Avertisseur sonore:	Buzzer Volume réglable
Characterstics DE PERFORMANCE	
Largeur de champ de balayage:	60mm @ 30mm (De visage du moteur) 98mm @ 100mm (de la face du moteur)
Profondeur de champ de balayage:	10-450mm (Contraste 0,9 Densité 0,25)
Vitesse de numérisation:	150 scans / sec
Précision de numérisation:	0.10-0.825mm
Bit Error Rate:	1500000)
Capacité de Décodage:	UPC / EAN, UPC / EAN avec Supplementals, UCC / EAN128, Code39, Code 39 ASCII complet, Trioptic Code 39, Code 128, Code 128 ASCII complet, Codabar, Interleaved 2 of 5, Discrete 2 5, Code 93, MSI, code 11, RSS variantes, chinois 2 de 5, MSI / Plessey, Royaume-Uni / Plessey, UCC / EAN 128, code chinois, GS1 DataBar (RSS) série
Batterie:	3.7V / 750mAh, Li-ion
Temps de charge:	3.0 Heures
Scan Time:	30 Heures
Courant:	95mA (travail); 25mA (veille)
Angles:	Pitch: 60 °; Tilt: 45 °
Fréquence de travail:	433MHz
Distance de communication:	200m (Ouvert Places)
Interface de communication:	USB
Characterstics ENVIRONNEMENT UTILISATEUR	
Température:	-10degree Cto 45degré C (Fonctionnement), -40degree Cto 60degree C (stockage)
Humidité relative:	5% -90% (sans condensation)
Baisse Spécifications:	Résiste 1.5m répétée tombe à la surface du béton
Illumination ambiante:	0 ~ 100.000 LUX
Décharge électrostatique:	Conforme à ± 12KV évacuation de l'air et de ± 6KV de décharge de contact
Certificat de sécurité:	CE, FCC, classe 2, RoHS

## Détails du produit:



## Wireless Barcode Scanner

OCBS-W800



### Product Picture





## Features

**Simple but not easy**

Integrated non-volatile memory



Data transmission distance reaches 200m in open area



Integrated non-volatile memory



Intelligent battery management system, real-time check the remaining battery



32bit decoder ensuring excellent decoding ability



### All-round show





## Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm
Memory	128K
Scanner Dimensions(W * H * D)	168mm * 72mm * 93mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	370g
Scanning Mode	Hand-held; Continuous Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm (From engine face) 98mm@100mm (from engine face)
Depth of Scan Field	10-450mm (Contrast 0.9 Density 0.25)
Scan Speed	150 scans/sec

Scan Precision	0.10-0.825mm
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese Code, GS1 DataBar (RSS) series
Battery	3.7V/750mAh, Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	95mA (working); 25mA(standby)
Angles	Pitch:60°; Tilt: 45°
Working Frequency	433MHz
Communication Distance	200m (Open Places)
Communication Interface	USB
<b>USER ENVIRONMENT CHARACTERISTICS</b>	
Temperature	-10°C to 45°C (Operating), -40°C to 60°C (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at [www.ocominc.com](http://www.ocominc.com), Together we quest for the best.



### Documents pertinents:

Voulez-vous en savoir plus .inf produitormation?S'il vous plaît Cliquez ici.

[spécification](#)

[Manuel d'utilisation](#)