

## OCBS-W800 433MHz sans fil scanner de codes à barres portable avec mémoire

### CARACTÉRISTIQUES:

characterstics PHYSIQUES	
Source de lumière:	Diode Laser Visible (VLD) @ 650 nm
Scanner Dimensions :	168mm * 72mm * 93mm (W * H * D)
Dimensions du récepteur:	130mm * 45mm * 129mm (W * H * D)
Matériel:	ABS + TPR / alliage d'aluminium
Poids:	370g
Mode de numérisation:	À main; Mode balayage continu.
Voyant:	LED rouge et bleu
Avertisseur sonore:	Buzzer Volume réglable
Characterstics DE PERFORMANCE	
Largeur de champ de balayage:	60mm @ 30mm (De visage du moteur) 98mm @ 100mm (de la face du moteur)
Profondeur de champ de balayage:	10-450mm (Contraste 0,9 Densité 0,25)
Vitesse de numérisation:	150 scans / sec
Précision de numérisation:	0.10-0.825mm
Bit Error Rate:	1500000)
Capacité de Décodage:	UPC / EAN, UPC / EAN avec Supplementals, UCC / EAN128, Code39, Code 39 ASCII complet, Trioptic Code 39, Code 128, Code 128 ASCII complet, Codabar, Interleaved 2 of 5, Discrete 2 5, Code 93, MSI, code 11, RSS variantes, chinois 2 de 5, MSI / Plessey, Royaume-Uni / Plessey, UCC / EAN 128, code chinois, GS1 DataBar (RSS) série
Batterie:	3.7V / 750mAh, Li-ion
Temps de charge:	3.0 Heures
Scan Time:	30 Heures
Courant:	95mA (travail); 25mA (veille)
Angles:	Pitch: 60 °; Tilt: 45 °
Fréquence de travail:	433MHz
Distance de communication:	200m (Ouvert Places)
Interface de communication:	USB
Characterstics ENVIRONNEMENT UTILISATEUR	
Température:	-10degree Cto 45degré C (Fonctionnement), -40degree Cto 60degree C (stockage)
Humidité relative:	5% -90% (sans condensation)
Baisse Spécifications:	Résiste 1.5m répétée tombe à la surface du béton
Illumination ambiante:	0 ~ 100.000 LUX
Décharge électrostatique:	Conforme à ± 12KV évacuation de l'air et de ± 6KV de décharge de contact
Certificat de sécurité:	CE, FCC, classe 2, RoHS

### Détails du produit:



## Wireless Barcode Scanner

OCBS-W800



### Product Picture





## Features

**Simple but not easy**

Integrated non-volatile memory



Data transmission distance reaches 200m in open area



Integrated non-volatile memory



Intelligent battery management system, real-time check the remaining battery



32bit decoder ensuring excellent decoding ability



### All-round show





## Parameter

PHYSICAL CHARACTERISTICS	
Light Source	Visible Laser Diode (VLD) @ 650 nm
Memory	128K
Scanner Dimensions(W * H * D)	168mm * 72mm * 93mm
Receiver Dimensions(W * H * D)	130mm*45mm*129mm
Material	ABS+TPR /Aluminium alloy
Weight	370g
Scanning Mode	Hand-held; Continuous Scanning Mode.
Indicator Light	LED Red and Blue
Buzzer	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
Width of Scan Field	60mm@30mm (From engine face) 98mm@100mm (from engine face)
Depth of Scan Field	10-450mm (Contrast 0.9 Density 0.25)
Scan Speed	150 scans/sec



Scan Precision	0.10-0.825mm
Bit Error Rate	1/(5million)
Decode Capability	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese Code, GS1 DataBar (RSS) series
Battery	3.7V/750mAh, Li-ion
Charge Time	3.0 Hours
Scan Time	30 Hours
Current	95mA (working); 25mA(standby)
Angles	Pitch:60°; Tilt: 45°
Working Frequency	433MHz
Communication Distance	200m (Open Places)
Communication Interface	USB
<b>USER ENVIRONMENT CHARACTERISTICS</b>	
Temperature	-10°C to 45°C (Operating), -40°C to 60°C (Storage)
Relative Humidity	5%-90%(Non-Condensing)
Drop Specification	Withstands repeated 1.5m drops to concrete surface
Ambient Illumination	0~100,000 LUX
Electrostatic Discharge	Conforms to ±12KV air discharge and ±6KV of contact discharge
Safety Certificate	CE, FCC, Class 2, RoHS

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow



### Documents pertinents:

Voulez-vous en savoir plus .inf produitormation?S'il vous plaît Cliquez ici. 

[spécification](#)

[Manuel d'utilisation](#)