

# 15.1 Inch Aluminium Alloy Touch POS Terminal

(M/N: POS -1513W& POS -1513A)



OCOM 1513 series POS terminal has aluminium alloy shell and base. It has Intel Celeron and Intel Core I series CPU for option. It is easy to install 2<sup>nd</sup> display, MSR, VFD as modules. This model is very convenient for maintenance by removing the back cover and it has rich I/O interfaces to be connected to more external devices.

## Caractéristiques:

- I Intel Celeron series and Intel Core I3 I5 processor for option
- I Rockchip high speed RK3288 processor for option
- I EMMC 8GB/16GB/32GB for option
- I Hard Drive M.2 SSD 64GB, SSD 128GB and 256 GB for option
- I Multi-point projected capacitive touch panel
- I Optional side MSR and VFD220 customer display mounted to back cover
- I True flat and water-proof scratch-resistant surface display

## Caractéristiques:

Modèle	POS -1513W	POS -1513A
Nom	15.1 inch aluminium alloy touch POS terminal	
Logement	aluminium alloy shell machine body and base	
Couleur	whole black color machine	
Affichage		
Écran principal	15.1 inch touch screen monitor	
Resoluiton	1024*768	
Luminosité	250cd/m <sup>2</sup>	
Angle de vue	Horizon: 160; Vertical :150	
Écran tactile	Multi-point projected G+G capacitive touch	
Sub-display	9.7 inch display W/o touch function	
Customer display	2*20 VFD or 2*20 LCD display mounted to back cover for option	
Performance		
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz usually or intel core I3 / I5 4 <sup>e</sup> generation CPU for option	Rockchip series RK3288 ,quad core 1.8G, RK3399 for option
Mémoire système	1*SO-DIMM DDRIII slot, support1333*/1600 4GB usually ,2GB/8GB for option	On board DDRIII 1GB,2GB,4GB for option
Périphérique de stockage	Msata SSD 64GB or higer, up to 256GB	on board8GB,16GB ,32GB EMMC for option
l'audio	On board Real Tek ALC662	on board Real Tek ALC5640 audio chip
LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module	10/100Mbs,Realtek RTL8111F Lan chip□Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support
Système opérateur	Windows7/8/10, Embedded,WE POS ,Linux	Up to Android 8.1
Connectivity		

Externe I/O port(J1900/RK3288)	power button*1
	12V DC in jack*1
	LAN:RJ-45*1
	USB*4
Externe I/O port J1900	15PIN D-sub VGA *1
	HDMI*1 or RS 232*1 for option
	line out*1,MIC in*1
Externe I/O port RK3288	Audio out*1
	TF card port*1
	RJ11 for cash drawer*1
	RS 232*1
Options	
MSR	optional side MSR
Environnement	
Operating temperature	0 to 40 degrees centigrade
Température de stockage	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Emballer	
Masse	Net 5.5Kg, Gross 7.0Kg
Package with foam inside	440*290*425mm
Accessoires	
Adaptateur secteur	110-240V/50-60HZ AC power input ,DC12V/5A output adaptor
Câble d'alimentation	Power cable plug compatible with USA /EU / UK etc and customized available
Autre	
Conformité	FCC Class A/CE Mark/LVD/CCC