

Android Pos Terminal Pos Machine Touch Screen All in One Pos System with Cash Register

(M/N: POS -H156W/A-H151W/A)



OCOM H series pos integrated high speed thermal printer and scanner module inside,it is a kind of cost-effective machine for using, different frame colors make machine more beautiful, extended IO interface make a few more external devices connected, newly designed rear cover which can be easily removed without tools for faster installation and maintenance.

Caractéristiques:

Intel Celeron series and intel core I3 I5 processor for option

Rockchip high speed RK3288 processor

EMMC 8GB/16GB/32GB for option

Hard Driver Msata SSD 64GB ,SSD 128GB an 256 GB for option

58mm and 80mm high speed thermal printer built in for option

Multi-point projected capacitive touch panel

Optional side MSR and VFD220 customer display mounted to back cover

Bar-code scanner inbuilt for option

True flat and water-proof/scratch-resistant surface display

Caractéristiques:

Modèle	POS -H156	POS -H151
Nom	15.6 inch all in one touch screen pos terminal	15.1 inch all in one touch screen pos terminal
Logement	plastic with metal combined	
Couleur	white machine body or black machine body match orange or blue frame colors	
Affichage		
Écran principal	15.6 inch touch screen monitor	15.1 inch touch screen monitor
Résolution	1366*768	1024*768
Luminosité	250cd/m ²	
Angle de vue	Horizon: 150; Vertical :140	
Écran tactile	Multi-point projected G+G capacitive touch	
Sub-display	15.6/14/11.6 inch display W/ or W/o touch function, resolution 1366*768 for optional	15.1 inch display W/ or W/o touch function, resolution 1024*768
Customer display performance	2*20 VFD mounted to back cover for option	
Windows J1900	Motherboard	Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4 ^e generation CPU for option
	Mémoire système	1*SO-DIMM DDRIII slot, support 1333*/1600 2GB/4GB/8GB for option
	Périphérique de stockage	Msata SSD 64GB or higer, up to 256GB
	l'audio	On board Real Tek ALC662 audio chip
	LAN	10/100Mbs, Realtek RTL8111F Lan chip built in Mini PCI-E slot, support embedded WIFI module
	Système opérateur	Windows 7/8/10, Embedded, WE POS ,Linux

Android RK3288	Motherboard	Rockchip series RK3288 ,quad core 1.8G, RK3399 for optional
	Mémoire système	On board DDRIII 2GB,4GB for option
	Périphérique de stockage	On board 16GB EMMC,32GB for option
	l'audio	On board Real Tek ALC5640 audio chip
	LAN	10/100Mbs,Realtek RTL8111F Lan chip
	WIFI&BT module	Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support
	Système opérateur	Android 7.1
Connectivity		
Windows/Android(J1900&RK3288)	power button*1	
	12V DC in jack*1	
	LAN:RJ-45*1	
	USB *6	
	MIC in*1, Audio out*1	
Windows(J1900)	COM(RS232) *1 or HDMI*1 for option	
	VGA(15Pin D-sub)*1	
	RJ11 for Cash drawer *1 for option	
Android(RK3288)	COM(RS232) *1	
	On board RJ11 for Cash drawer *1 ,RJ11 from printer port for cash drawer*1(optional)	
	TF card slot*1	
Options		
80mm thermal printer	direct thermal printing	
	100mm/s printing speed	
	79.5-/+ 0.5mm paper width and printable width 72mm	
	with auto cutter function and thermal head life 50km	
	LPT communication	
58mm thermal printer	direct thermal printing	
	85mm/s printing speed	
	57.5-/+ 0.5mm paper width and printable width 48mm	
	thermal head life 50km	
	LPT communication	
MSR	optional side MSR	
webcam	web camera mounted on top of the display for option	
Scanner	support 1D&2D code-scanning for option	

Conférencier	4ohm/5w speakers inside for option
Emballer	emballer
Masse	net 5.6Kg , gross:7.7Kg for 15.6 with 15.6 dual screen /no printer built in
Package with foam inside	340*450*480mm
2in1 carton	700*460*500mm /gross 17Kg
Environnement	
Operating temperature	0 to 40 degrees centigrade
Température de stockage	-10 to 60 degrees centigrade
Working humidity	10%~80%
Storage humidity	10%~90%
Accessoires	
Adaptateur secteur	110-240V/50-60HZ AC power input ,DC12/5A output adaptor for W/o printer and W/ 58mm printer machine DC12V/7A out put adaptor only for W/ 80mm printer machine
Câble d'alimentation	Power cable plug compatible with USA /EU / UK etc and customized available
CD driver	Pilote de la carte mère et pilote tactile à l'intérieur pour option
Autre	
Conformité	Marquage de classe A / CE FCC / LVD / CCC

Plus d'images de produit montrées



Pas besoin d'outils pour éliminer la couverture arrière, très pratique pour la mise à niveau de RAM / SSD par des clients et de la facilité



Les ports USB latéraux font de la machine en téléchargement et en téléchargement plus facilement



Ports d'IO externes



Emballer

