

# 15.6 or 15.1 Inch All In One Touch POS Terminal

(M/N: POS -H156W/A-H151W/A)



OCOM H series pos integrated high speed thermal printer and scanner module inside, it is a kind of cost-effective machine for using, different frame colors make machine more beautiful, extended IO interface make a few more external devices connected, newly designed rear cover which can be easily removed without tools for faster installation and maintenance.

## **Caractéristiques:**

Intel Celeron Series e Intel Core I3 I5 Processore per opzione

Processore RK3288 ad alta velocità RockChip

EMMC 8 GB / 16 GB / 32 GB per opzione

Driver hard msata SSD 64GB, SSD 128GB un 256 GB per opzione

Stampante termica ad alta velocità da 58 mm e 80 mm integrata per opzione

Pannello tattile capacitivo proiettato multi-punto

Lato opzionale MSR e VFD220 visualizzano il display del cliente montato sul coperchio pos teriore

Scanner per bar-codici integrato per opzione

Display SureFace TRUE e ACQUA / RESISTENTE RESISTENTE RESISTENTE

**Caractéristiques:**

Modèle	POS -H156	POS -H151
Prénom	15.6 inch all in one touch screen pos terminal	15.1 inch all in one touch screen pos terminal
Logement	plastic with metal combined	
Couleur	white machine body or black machine body match orange or blue frame colors	
Filtrer		
Écran principal	15.6 inch touch screen monitor	Monitor touch screen da 15.1 pollici
Résolution	1366*768	1024 * 768.
Luminosité	250cd / M. <sup>2</sup> .	
Vista ad angolo	Horizon: 150; Vertical :140	
Écran tactile	Tocco capacitivo di G + G del multi-punto	
Sotto-es posizione	15.6/14/11.6 inch display W/ or W/o touch function, resolution 1366*768 for optional	15.1 inch display W/ or W/o touch function, resolution 1024*768
Visualizzazione del cliente	2*20 VFD mounted to back cover for option	
performance		
Windows J1900	Carte mère	Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4 <sup>th</sup> . CPU di generazione per opzione
	Mémoire système	1*SO-DIMM DDRIII slot, support1333*/1600 2GB/4GB/8GB for option
	Dis pos itivo di archiviazione	Msata SSD 64 GB o Higer, fino a 256 GB
	l'audio	On board Real Tek ALC662 audio chip
	LAN	10 / 100mbs, Realtek RTL8111F LAN Chip Slot mini PCI-E integrato, supporto Modulo WiFi incorporato
	Système opérateur	Windows7/8/10, Embedded,WE POS ,Linux

Android RK3288	Carte mère	Rockchip series RK3288 ,quad core 1.8G, RK3399 for optional
	Mémoire système	On board DDRIII 2GB,4GB for option
	Dis pos itivo di archiviazione	On board 16GB EMMC,32GB for option
	l'audio	On board Real Tek ALC5640 audio chip
	LAN	10 / 100mbs, Realtek RTL8111F LAN Chip
	WIFI&BT module	Support Wi-Fi 802.11b/g/n,BT3.0/BT4.0 support
	Système opérateur	Android 7.1
Connettività		
Windows/Android(J1900&RK3288)	Pulsante di accensione * 1	
	12V DC in Jack * 1	
	LAN: RJ-45 * 1	
	USB *6	
	MIC in*1, Audio out*1	
Windows(J1900)	COM(RS232) *1 or HDMI*1 for option	
	VGA(15Pin D-sub)*1	
	RJ11 for Cash drawer *1 for option	
Android(RK3288)	COM(RS232) *1	
	On board RJ11 for Cash drawer *1 ,RJ11 from printer port for cash drawer*1(optional)	
	TF card slot*1	
Opzioni		
80mm thermal printer	direct thermal printing	
	100mm/s printing speed	
	79.5-/+ 0.5mm paper width and printable width 72mm	
	with auto cutter function and thermal head life 50km	
	LPT communication	
58mm thermal printer	direct thermal printing	
	85mm/s printing speed	
	57.5-/+ 0.5mm paper width and printable width 48mm	
	thermal head life 50km	
	LPT communication	
Msr.	lato opzionale MSR.	
web camera	web camera mounted on top of the display for option	
Scanner	support 1D&2D code-scanning for option	

Conférencier	4ohm/5w speakers inside for option
Emballer	emballer
Masse	net□5.6Kg , gross:7.7Kg for 15.6 with15.6 dual screen /no printer built in
Confezione con schiuma dentro	340*450*480mm
2in1 carton	700*460*500mm /gross□17Kg
Environnement	
Temperatura di esercizio	0 a 40 gradi centigradi
Température de stockage	-10 a 60 gradi centigradi
Umidità lavorativa	10%~80%
Umidità di stoccaggio	10%~90%
Accessoires	
Adaptateur secteur	110-240V / 50-60HZ AC PowerInput, adaptateur de sortie DC12 / 5A pour l'imprimante W / O et la machine d'imprimante W / 58mm DC12V / 7A OUT OUT OUT OUT UNIQUEMENT POUR LA MACHINE D'IMPRIMANTE W / 80MM
Cordon d'alimentation	Cordon d'alimentation Compatible avec USA / UE / UK, etc. Et personnalisé
Conducteur de CD	Pilote de la carte mère et pilotes tactiles à l'intérieur de l'option
Autre	
Conformité	Signe de classe de classe A / CE / CCC FCC / CCC

Plus d'images des produits présentés



Pas besoin d'outils pour supprimer la couverture de Time3 pos, très confortablement pour la mise à jour de la RAM / SSD et de la maintenance des clients



Les ports USB latéraux rendent la machine plus facilement télécharger et décharger



Portes externes



Emballer

