

Pos receipt pos ticket printer  
(OCP-80G)

**Features:**

receipt pos printer, ticket printer, pos receipt printer

1. Desktop or wall-mounted type for option.
2. Supports multi 1D barcodes and QR codes printing.
3. 100M Ethernet port, ultra high speed data transmission.
4. Supports 256KB NV Logo storage and 2M big buffer memory.
5. Supports black mark detection and order reminding function, compatible with OPOS driver.
6. Supports printing status monitor and anti-losing order function.
7. 3 interface 260mm/s printing Speed

**Parameters:**

receipt pos printer, ticket printer, pos receipt printer

|                      |                                                                                                                                                                                                                                |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Printing method:     | Direct thermal                                                                                                                                                                                                                 |
| Printing speed:      | 230mm/s □260mm/s                                                                                                                                                                                                               |
| Roll width:          | 79.5±0.5mm                                                                                                                                                                                                                     |
| Print diameter:      | Φ80mm                                                                                                                                                                                                                          |
| Paper thickness:     | 0.06-0.08mm                                                                                                                                                                                                                    |
| Column capacity:     | 576dots/line512 Dots/line                                                                                                                                                                                                      |
| Line's pacing :      | 3.75mm□Adjustable by commands□                                                                                                                                                                                                 |
| Print command:       | Compatible with the ESC/POS command                                                                                                                                                                                            |
| Interface type:      | Serial+USB+Lan/36P parallel port/25P serial +USB/LAN                                                                                                                                                                           |
| Cutters life:        | 1million cuts                                                                                                                                                                                                                  |
| Print head life:     | 100 km                                                                                                                                                                                                                         |
| Input buffer :       | 2048Kbytes                                                                                                                                                                                                                     |
| NV Flash:            | 256Kbytes                                                                                                                                                                                                                      |
| Power adaptor:       | AC110V/240V□50~60Hz                                                                                                                                                                                                            |
| Power supply:        | DC 24V/2.5A                                                                                                                                                                                                                    |
| Cash drawer supply:  | DC 24V/1A                                                                                                                                                                                                                      |
| Work environment:    | Temperature(0□45) humidity(10□80%)□Non- condense□                                                                                                                                                                              |
| Work environment:    | Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense                                                                                                                                                            |
| Storage environment: | Temperature(-10□60℃); Humidity(10□90%)                                                                                                                                                                                         |
| Character size:      | ANK□FontA:1.5*3.0mm/ FontB□1.1*2.1mm                                                                                                                                                                                           |
| Barcode:             | UPC-A/UPC-E/JA□EAN13□JAN8□EAN8/CODE39/ITF /CODE93/CODE128/QRCode/PDF417 (options)                                                                                                                                              |
| Characters:          | PC347□Standard Europe□Katakana□PC850□Multilingual□PC860□Portuguese□PC863 □Canadian-French□PC865□Nordic□West Europe□Greek□Hebrew□East Europe□Iran□WPC1252□PC866□Cyrillic#2□PC852□Latin2□PC858□IranII□Latvian□Arabic□PT151□1251□ |

Physical  
characteristics□

Weight: 1.25Kg; Appearance size: 190×145×143mm (length \* width \* height)

**Product Show:**

receipt pos printer,ticket printer,pos receipt printer





[www.ocominc.com](http://www.ocominc.com)





[www.ocominc.com](http://www.ocominc.com)

CE FCC





### Relevant documents:

[\\*Specification](#)

[\\*IP Address Configure Manual](#)

[\\*Instruction Manual](#)

[\\*Driver for all windows system](#)

[\\*Driver for Linux](#)

[\\*Printer Parameters Setting Tools](#)

\*CD Files